This form is <u>not</u> to be ised for reporting acker leakage tests n Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

Page 1

northwest new mexico packer leakage test

Pevised June 10, 2003

bp	America Prod 10 Energy Cour	uction Compan	y . NM 87401	Lease Na	ame _	Bolack	Well No. \M			
	Well: Unit Letter						5-24989			
	Name of Reservoir or Pool		Type of Prod.		N	Aethod of Prod.	Prod. Medium			
			(Oil or Gas)		(F	low or Art. Lift)	(Tbg. Or Csg.)			
Upper Completion	Blanco MV		GAS			FLOW	TBG .			
Lower			9,10			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				
Completion	Basin F)K	GAS			FLOW	TRG			
Pre-Flow Shut-In Pressure Data										
Upper	Hour, Date, Shu			Length of Time Shut-In		Press. Psig	Stabilized? (Yes or No)			
Completion	9/18/07		72 HOURS			ຂ ຊ ລັ	YES			
Lower Completion	Hour, Date, Shut-In		Length of Time Shut-In 72 HOURS		SI	Press. Psig くいし	Stabilized? (Yes or No) YES			
Flow Test No. 1 RCVD NOV 13 '07										
Commenced	at (hour, date)*		Zone producing (Unper or Lower):							
Time						Remarks	<u> </u>			
(Hour, Date)		Upper Compl.	Lower Compl.	Temp		Remarks	DST. 2			
9/18	DAY 1	290	274			BOTH ZONES	SHUT IN			
9/19	DAY 2	291	367			BOTH ZONES	SHUT IN			
9/20	DAY 3	७ ९२	406			BOTH ZONES	SHUT IN			
9/21	DAY 4	293	272			FLOW Lowe,	ZONE			
9/22	DAY 5	294	234			FLOW "	ZONE			
9/23	DAY 6	ચ વય	231			FLOW "	ZONE			
roduction rat	e during test									
Dil:BOPD based onBbls. InHrsGravGOR										
ras: MCFPD; Test thru (Orifice or Meter):										
Mid-Test Shut-In Pressure Data										
Upper Completion	the state of the s		Length of Time Shut-In			ress. Psig	Stabilized? (Yes or No)			
Lower Completion	Hour, Date, Shut-In		Length of Time Shut-In		SI Press. Psig		Stabilized? (Yes or No)			

(Continue on reverse side)

Flow Test No. 2

Commenced a	at (hour, date)**		Z	one producing (U	Jpper or Lower):	
Time	Lapsed Time	<u>Pr</u>	essure	Prod. Zone		
(Hour, Date)	Since**	Upper Compl.	Lower Compl.	Temp.		
					-	
Production rate	during test		<u> </u>	— L		
Oil:	BOPD based	l on	Bbls. In	Hrs	Grav GOR	
	MCFPI	D; Test thru (Ori	fice or Meter):			
Remarks:			,			
hereby certify	that the informati	ion herein contain	ned is true and con	nplete to the best	of my knowledge.	
Approved	1.01		20		p America Production Company	
Jarr. Marriago O	il Conservation D			San Juan OC - Farmington Office		
H. Vil	lanueva		ByS	heri Bradshaw 😘		
Зу				Title	Tield Tech	
Title	Deputy Oil ————————————————————————————————————	& Gas Inspec strict #3	E-mail Address sheri.bradshaw@bo.com			
		•	•	Date	10/02/07	

Northwest New Mexico Packer Leakage Test Instructions

A packer leakage test shall be commenced on each multiply ompleted well within seven days after actual completion of the well, and anually thereafter as prescribed by the order authorizing the multiple ompletion. Such tests shall also be commenced on all multiple ompletions within seven days following recompletion and/or chemical r fracture treatment, and whenever remedial work has been done on a ell during which the packer or the tubing have been disturbed. Tests hall also be taken at any time that communication is suspected or when equested by the Division.

At least 72 hours prior to the commencement of any packer leakage st, the operator shall notify the Division in writing of the exact time the st is to be commenced. Offset operators shall also be so notified.

The packer leakage test shall commence when both zones of the dual impletion are shut-in for pressure stabilization. Both zones shall remain nut-in until the well-head pressure in each has stabilized, provided owever, that they need not remain shut-in more than seven days.

For Flow Test No. 1, one zone of the dual completion shall be roduced at the normal rate of production while the other zone remains ut-in. Such test shall be continued for seven days in case of a gas well id 24 hours in the case of an oil well. Note: if, on an initial packer akage test, a gas well is being flowed to the atmosphere due to the lack a pipeline connection the flow period shall be three hours.

Following completion of Flow Test No. 1, the well shall again be ut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).