

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

RCVD OCT 25 '07

Sundry Notices and Reports on Wells

OIL CONS. DIV.

DIST. 3

1. Type of Well  
GAS

2. Name of Operator

**BURLINGTON**

RESOURCES OIL &amp; GAS COMPANY LP

3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit I (NESE), 1775' FSL &amp; 660' FEL, Section 12, T28N, R8W, NMPM

5. Lease Number  
SF-078390-A
6. If Indian, All. or  
Tribe Name
7. Unit Agreement Name
8. Well Name & Number  
Price #5M
9. API Well No.  
30-045-34160
10. Field and Pool  
Basin Dakota  
Blanco Mesaverde
11. County and State  
San Juan Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission

Type of Action

☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

9/28/07 MIRU HP 283. NU BOP. PT csg to 600psi for 30 mins @ 04:30am on 9/29/07. RIH w/ 8 3/4" bit & tag TOC @ 194'. DO cmt & drill ahead to 3330'. Circ hole. RIH w/80jts 7" J-55 20# STC csg set @ 3308'. Circ. Pumped in preflush of 20bbls mudflush & 2bbls H2O. Pumped in LEAD 411sx (878cf - 156bbls) Premium Lite FM cmt w/.4% Sodium Metasilicate, 3% CaCl, 5pps LCM-1, 8% Bentonite, .4% FL-52A & .25pps Cello-Flake. Followed w/TAIR 72sx (101cf- 18bbls) Type III cmt w/1%CaCl, .2% FL-52A & .25pps Cello-Flake. Drop plug & displaced w/132bbls H2O. Bump plug w/1670 psi. Circ 72bbls cmt to surface @ 11:30am on 10/2/07. WOC. PT csg to 1500psi for 30mins @ 20:00hr on 10/2/07.

10/2/07 RIH w/6 1/4" bit & tag TOC @ 3266'. DO cmt & drill ahead to 7554' TD. TD reached 10/4/07. Circ hole. RIH w/181 jts 4 1/2" J-55 (14jts 11.6 LTC & 167jts 10.5 STC) csg & set @ 7530'. Circ hole. Pumped in preflush of 20bbls chem wash & 2bbls FW. Pumped in 321sx (636cf - 113bbls) Premium Lite HS FM cmt w/.25pps Cello-Flake, 6.25pps LCM-1, 1% FL-52A & .3% CD-32. Drop plug & displaced w/120bbls FW w/25# sugar in first 10bbls. Bump plug w/1600 psi @ 03:30am on 10/5/07. ND BOP. RD RR @ 08:00am on 10/5/07.

PT will be conducted by the completion rig and results shown on next report. TOC will be reported on next report.

**14. I hereby certify that the foregoing is true and correct.**Signed Tamra Sessions Tamra Sessions Title Regulatory Technician Date 10/10/07

ACCEPTED FOR RECORD

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date OCT 22 2007

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

FARMINGTON FIELD OFFICE  
BY [Signature]

NMOCDO