

H2A 30-039-21237

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit P Sec. 02 Twp. 26 Rng. 03

Name of Well/Wells. or Pipeline Serviced _____

JICATILLA 96 #2A

Elevation _____ Completion Date 6-6-95 Total Depth _____ Land Type I

Casing Strings, Sizes, Types & Depths 4 1/2 SET 179' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 32 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. 180' - Fresh, Clear

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 470' 4900/lbs

Asbury

Depths anodes placed: 440, 432, 426, 407, 401, 395, 368, 343, 335, 310, 258, 252, 246, 240, 234

Depths vent pipes placed: Surface to 470'

Vent pipe perforations: From 200' to 470'

Remarks: _____

RECEIVED
JAN 11 1996

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.