

#6 30-039-25394

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit J Sec. 04 Twp 24 Rng 03

Name of Well/Wells or Pipeline Serviced _____

Cullins Federal #6

Elevation 7057 Completion Date 6/5/95 Total Depth 469' Land Type F

Casing Strings, Sizes, Types & Depths 4 1/2 Set 98' of 8" PVC Casing.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. HIT FRESH WATER AT 145', AND A MAJOR FRESH WATER VEIN AT 390'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 469' Depth.

Used 122 SACKS OF ASBURY 218R (6100#)

Depths anodes placed: 425', 375', 363', 355', 345', 300', 277', 269', 261', 253', 230', 220', 185', 177', + 169'.

Depths vent pipes placed: SURFACE TO 469'.

Vent pipe perforations: BOTTOM 340'.

Remarks: _____

RECEIVED
JAN 11 1996

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.