## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RCVD DEC 14'07 OIL CONS. DIV. DIST. 3

Sundry Notices and Reports	on Wells		
	RECEIVED	5.	Lease Number NMSF-080750
1. Type of Well GAS	DEC 1 2 2007	6.	If Indian, All. or Tribe Name
2. Name of Operator BURLINGTON	Bureau of Land Management Farmington Field Office	7.	Unit Agreement Name
RESOURCES OIL & G	GAS COMPANY LP	0	********
3. Address & Phone No. of Operator		<del></del> 8.	Well Name & Number Sunray F 1F
PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	API Well No.
4. Location of Well, Footage, Sec., T, R, M			30-045-34450
		10.	Field and Pool
Unit I (NESE), 2565' FSL & 885' FEL, Section 26, T30N R10W, NMPM			Basin Dakota
		11.	County and State San Juan Co., NM
Tinal Abandonment  13. Describe Proposed or Completed (12/1/07 H&P 281. RIH w/ 8 ¾" bit tagg 7", 23#, J-55 ST&C csg & set @ 4753' & (469 cf – 105 bbls slurry) Premium Lite 5#/sx LCM-1, .4% Sodium Metasilicate. FL-52A, 1% GW 3LD, 6.25#/sx LCM-1 1847 hrs on 12/6/07. Circ 5 bbls cmt to s	ged on cmt, D/O cmt & drilled ahead to 4753' inter & set DV tool @ 2158' Preflush w/20 bbls mudw FM, w/3% Calcium Chloride, 8% Bentonite, .25# Tail 112 sx (155 cf – 27 bbls slurry) Type III.39 . Dropped plug & displaced w/40 bbls FW & 117 surface. Stage 2 pre-flushed w/20 bbls mudwash.	ash 10 bbls FV/sx Cellophane % CD-32, .25# bbls mud. Bu Lead 326 sx	W. Stage 1 Lead 220 sx e flakes, .4% FL-52A, t/sx Cellophane flakes, .2% umped plug to 1295# @ (694 cf – 123 bbls slurry)
displaced w/87 bbls FW. Bumped plug 12/7/07 Mist drilled out DV tool @ 2158 Reached 12/8/07. Circ hole. RIH w/179 bbls chemwash & 2 bbls FW. Pumped Cellophane flakes, 1% FL-52A, 6.25#/sx	ride,8% Bentonite, .25#/sx Cellophane flakes, .4% to 2610# @ 0001 hrs on 12/7/07. Circ 50 bbls cn 8'. PT csg to 1800#/30 mins – ok. RIH w/6 ¼" bi 9 jts, 4 ½", 10.5/11.6#, J-55 ST&C /LT&C csg & Tail 197 sx (390 cf – 67 bbls slurry) Premium Lite LCM-1. Dropped plug & displaced w/10 bbl sur BOP NU WH. RD release rig 0300 hrs 12/10/07	at to surface.  It & drilled and set @ 7393'.  HS FM, w/.3  Fgar water & 1	WOC.  ead to 7394' (TD). TD  Pre-flushed w/10 % CD-32, .25#/sx
PT will be conducted by completion rig a 14. I hereby certify that the foregoing	and reported on next report. TOC will be reported is true and correct.	l on next repor	
Signed Month St	Rhonda Rogers Title Regulato	ry Technician	Date 12/10/07 .
(This space for Federal or State Office us APPROVED BY	Title		Date ACCEPTED FOR RELORD