Office District Case Case							
District II 120 South St. Francis Dr. 1220 Fr							
1301 W. Grand Ave, Artesia, NM 88210							
1220 SOURT St. Plantes Dr. 1220 St. Plantes Dr. 1220 Sourt St. Plantes Dr. 1220 St. Pl							
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS CDO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPER NOR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) To Use a subject of the proposal of the							
SUNDRY NOTICES AND REPORTS ON WELLS ON NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROFOSALS.) 1. Type of Well: Oil Well Gas Well X Other 9. OGRID Number 14538 2. Name of Operator 9. OGRID Number 14538 3. Address of Operator 9. OGRID Number 14538 4. Well Location 16							
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:							
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well X Other State Unicon Com							
ROPERTON ROPERTOR							
Oil Well							
2. Name of Operator BURLINGTON RESOURCES OIL & GAS, LP 3. Address of Operator P.O. Box 4289, Farmington, NM 87499-4289 4. Well Location Unit Letter G: 2385' feet from the North line and 1530' feet from the East line Section 16 Township 28N Range 09W NMPM San Juan County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6408' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □ SUBSEQUENT REPORT OF: REMEDIAL WORK □ ALTERING CASING □ PULL OR ALTER CASING □ MULTIPLE □ CASING TEST AND CEMENT JOB OTHER: Casing report □ 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1220/07 H&P 283. RIH w% %" bit. Tagged cmt @ 157'. D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C cag & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1/201 of -214 bbls slurry) Premium Lite FW w/4% Sodium Metasilicate, 3% CACL2, 36% RB Most AcACL2, 28% CACL2, 36% CACL2, 36% CACL2, 36% CACL2, 36% CACL2, 36% CACL2, 36% CACLD,							
3. Address of Operator 14538 10. Pool name or Wildcat P.O. Box 4289, Farmington, NM 87499-4289 10. Pool name or Wildcat Basin Dakota / Blanco Mesaverde 4. Well Location Unit Letter G : 2385' feet from the North line and 1530' feet from the East line Section 16 Township 28N Range 09W NMPM San Juan County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6408' GL County 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB COMPLETION CHANGE PLANS COMPLETION CHANGE PLANS COMPLETION CHANGE PLANS COMPLETION CASING TEST AND CEMENT JOB COMPLETION CHANGE PLANS CASING TEST AND CEMENT JOB COMPLETION CHANGE PLANS CASING TEST AND CEMENT JOB COMPLETION CHANGE PLANS CASING TEST AND CEMENT JOB CASING TEST AND C							
P.O. Box 4289, Farmington, NM 87499-4289 Basin Dakota / Blanco Mesaverde							
4. Well Location Unit Letter G: 2385' feet from the North line and 1530' feet from the East line Section 16 Township 28N Range 09W NMPM San Juan County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6408' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: Casing report 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ½" bit. Tagged cmt @ 157'. D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C cas & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/4% Sodium Metasilicate, 3% CACL2, 5#/ss LCM-1, 8% Bentonite, 4% Fi-52A, 25# Cellophane							
Unit Letter G: 2385' feet from the North line and 1530' feet from the East line Section 16 Township 28N Range 09W NMPM San Juan County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6408' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS. ALTERING CASING DEMONSTRATED COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE COMPLETION CEMENT JOB OTHER: Casing report SITE CASING SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12720/07 H&P 283. RIH w/8 %" bit. Tagged cmt @ 157'. D/O cmt & drilled ahead to 4592' interm TD 12722/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C cas & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/4% Sodium Metastilicate, 3% CACL2, 5#/sx LCM-18, 3% Bentonic, 4% F1-52A, 25# Cellophane							
Section 16 Township 28N Range 09W NMPM San Juan County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6408' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS. ALTERING CASING CASING DEMENTION CASING EMENT JOB PULL OR ALTER CASING MULTIPLE CASING CASING CEMENT JOB OTHER: Casing report Casing report Casing any proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 %' bit. Tagged cmt @ 157'. D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, .4% F1-52A, .25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, 2.9% FL-52A, .25# Cello-phane							
Section 16 Township 28N Range 09W NMPM San Juan County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6408' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPNS. TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PULL OR ALTER CASING MULTIPLE CASING CASING CEMENT JOB OTHER: Casing report 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ½" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, .4% F1-52A, .25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, 2% FL-52A, .25# Cello-phane							
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6408' GL 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: OTHER: Casing report STATE OF							
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: Casing report S 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 %" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/. 4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, 4% FI-52A, .25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, .2% FL-52A, .25# Cellophane							
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □ REMEDIAL WORK □ ALTERING CASING □ TEMPORARILY ABANDON □ CHANGE PLANS □ COMMENCE DRILLING OPNS.□ PLUG AND ABANDONMENT PULL OR ALTER CASING □ MULTIPLE □ CASING TEST AND □ CEMENT JOB OTHER: □ OTHER: Casing report □ □ 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ¾" bit. Tagged cmt @ 157'. D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, .4% FI-52A, .25# Cello-flakes. Tail 106 sx (146 cf − 26 bbls slurry) Type III, w/1% CACL2, .2% FL-52A, .25# Cellophane							
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON ABANDON ABANDON ABANDON ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: Casing report CASING TEST AND CEMENT JOB OTHER: Casing report CASING TEST AND CEMENT JOB 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ¾" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, 4% FI-52A, 25# Cello- flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, 2% FL-52A, 25# Cellophane							
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON ABANDON ABANDON ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: Casing report CASING report COMPLETION COMPLETION COMPLETION COMPLETION CEMENT JOB 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ¾" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, 4% FI-52A, 25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, 2% FL-52A, 25# Cellophane							
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING MULTIPLE CASING TEST AND CEMENT JOB OTHER: Casing report 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ¼" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/14 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, 4% FI-52A, 25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, 2% FL-52A, 25# Cellophane							
PULL OR ALTER CASING MULTIPLE COMPLETION OTHER: Casing report OTHER: Casing report 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 %" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, 4% FI-52A, 25# Cello-flakes. Tail 106 sx (146 cf – 26 bbls slurry) Type III, w/1% CACL2, 2% FL-52A, .25# Cellophane							
PULL OR ALTER CASING							
OTHER: Casing report Casing report OTHER: Casing report Casing report Casing report OTHER: Casing report Casing repor							
OTHER: Casing report 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 %" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, 4% F1-52A, 25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, 2% FL-52A, .25# Cellophane							
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ¾" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, 4% FI-52A, .25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, .2% FL-52A, .25# Cellophane							
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 12/20/07 H&P 283. RIH w/8 ¾'' bit. Tagged cmt @ 157'. D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, .4% FI-52A, .25# Cello-flakes. Tail 106 sx (146 cf - 26 bbls slurry) Type III, w/1% CACL2, .2% FL-52A, .25# Cellophane							
or recompletion. 12/20/07 H&P 283. RiH w/8 ¼" bit. Tagged cmt @ 157'. D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RiH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, .4% FI-52A, .25# Cello-flakes. Tail 106 sx (146 cf – 26 bbls slurry) Type III, w/1% CACL2, .2% FL-52A, .25# Cellophane							
12/20/07 H&P 283. RÎH w/8 ¾" bit. Tagged cmt @ 157". D/O cmt & drilled ahead to 4592' interm TD 12/22/07. Circ hole. RIH w/114 jts, 7", 23#, J-55 LT&C csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, .4% Fl-52A, .25# Cello-flakes. Tail 106 sx (146 cf – 26 bbls slurry) Type III, w/1% CACL2, .2% FL-52A, .25# Cellophane							
csg & set @ 4566'. Pre-flush hole w/10 bbls FW & 10 bbls mud clean. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM w/.4% Sodium Metasilicate, 3% CACL2, 5#/sx LCM-1, 8% Bentonite, .4% Fl-52A, .25# Cello-flakes. Tail 106 sx (146 cf – 26 bbls slurry) Type III, w/1% CACL2, .2% FL-52A, .25# Cellophane							
12/26/07 RIH w/6 ¼" bit. Tagged cmt @ 4523'. D/O cmt & drilled ahead to 7280' (TD). TD reached 12/27/07. Circ hole. RIH w/174 jts, 4 ½", 10.5/11.6#, J-55							
ST&C/LT&C csg & set @ 7278'. Pre-flushed w/10 bbls chemwash & 2 bbls FW. Pumped Lead 211 sx (418 cf - 75 bbls slurry) Premium Lite HS FM, w/1%							
FL-52A, 6.25#/sx LCM-1, .3% CD-32, .25# Cellophane flakes. Dropped Plug & displaced w/116 bbl FW. Bumped plug to 1610#. ND BOP & NU WH. RD & released rig 12/28/07.							
PT will be conducted by the completion rig & reported on next report. TOC will be reported on next report.							
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-							
grade tank has been/wil) be constructed or closed according to NMOCD guidelines [], a general permit [] or an (attached) alternative OCD-approved plan [].							
SIGNATURE There TITLE Regulatory Specialist DATE 1/2/08							
SIGNATURE The Title Regulatory Specialist DATE 1/2/08 Type or print name Rhonda Rogers E-mail address: rogerrs@conocophillips.com Telephone No. 505-599-4018							
Type or print name Rhonda Rogers E-mail address: rogerrs@conocophillips.com Telephone No. 505-599-4018							
Type or print name Rhonda Rogers E-mail address: rogerrs@conocophillips.com Telephone No. 505-599-4018 (This space for State use)							
Type or print name Rhonda Rogers E-mail address: rogerrs@conocophillips.com Telephone No. 505-599-4018							

\$