

submitted in lieu of Form 3160-5
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RCVD JAN 7 '08
OIL CONS. DIV.
DIST. 3

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
BURLINGTON
RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit L (NWSW), 1530' FSL & 665' FWL, Section 3, T26N R9W, NMPM

RECEIVED

DEC 21 2007

Bureau of Land Management
Farmington Field Office

5. Lease Number
NMSF-078135
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
9. Huerfanito Unit 103F
API Well No.
30-045-34413
10. Field and Pool
Basin Dakota
11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

☒ Other - Casing Report

13. Describe Proposed or Completed Operations

11/25/07 MIRU Aztec 301. NU BOPE. PT csg to 600# 30/min - good test. RIH w/7 7/8" bit. Tagged cement @ 288'. D/O cement & ahead to 6844' (TD) TD reached on 12/1/07. RIH w/160 jts 4 1/2" 11.6# L-80 csg set @ 6834'. Circ hole. RU to cement. 12/9/07 Pumped pre-flush of 10 bbls Gel spacer/ 5 bbls FW. Pumped Scavenger 19 sx(61cf- 11bbls) Premium Lite HS FM Cement w/2% KCL, .3% CD-32, 1% FL-52, .25 #/sx Cello-Flake, & .3% R-3. Lead-Pumped 667 sx (1774cf - 315 bbls) Premium Lite HS FM Cement w/2% KCL, .3% CD-32, 1% FL-52, .25 #/sx Cello-Flake, & .3% R-3. Tail- pumped 294 sx(473cf-84bbls) 50/50 POZ Z Type III Cement w/.1% R-3, .2% Cd-32, .8% Fl-52, 2% Bentonite & 3.5 #/sx Pheno Seal. Dropped plug & displaced w/106 bbls FW. Bumped plug to 2130#. Plug down @ 05:20 on 12/10/07. RD cementers. 12/10/07 ND BOPE. RR @ 11:30 on 12/10/07 *Provide top of cement*

PT will be conducted by completion rig & results shown on next report. ✓

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 12/21/07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD

JAN 02 2008

FARMINGTON FIELD OFFICE
BY T. Salyers