

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-039-23388
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-291-5
7. Lease Name or Unit Agreement Name Canyon Largo Unit
8. Well Number 335
9. OGRID Number 208706
10. Pool name or Wildcat Devils Fork Gallup

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Huntington Energy, L.L.C.

3. Address of Operator
908 N.W. 71st St., Oklahoma City, OK 73116

4. Well Location
Unit Letter F : 1620 feet from the North line and 1750 feet from the West line
Section 32 Township 25N Range 6W NMPM Rio Arriba County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
6798' KB

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Huntington Energy, L.L.C. plans to plug and abandon the above referenced well. A procedure to plug & abandon along with a wellbore diagram are attached. The plugging procedure will take place upon availability of services.

RCVD JAN 16 '08

OIL CONS. DIV.

DIST. 3

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Catherine Smith TITLE Regulatory DATE 1/14/2008

Type or print name Catherine Smith E-mail address: csmith@huntingtonenergy.com Telephone No. (405) 840-9876

For State Use Only

Deputy Oil & Gas Inspector,
District #3

APPROVED BY: H. Villanueva TITLE _____ DATE JAN 18 2008

Conditions of Approval (if any): Note added plugs - see next page

Gave OCD 24/hr Notice to witness.

HUNTINGTON ENERGY, L.L.C.
908 N.W. 71ST ST.
OKLAHOMA CITY, OK 73116
(405) 840-9876

Canyon Largo Unit # 335
Sec 32-25N-6W
Rio Arriba Co., NM

Plugging Procedure:

1. POOH w/ 2 3/8" tubing.
2. RIH w/wireline. Set CIBP @ 5900'. Dump ^{35' is dumped} 20' cmt on plug. _{50' pumped}
- ~~3.~~ RIH w/tubing to 1900'. Spot 25 sx cmt (6 bbls) – est TOC 1550'.
- ~~4.~~ PUH w/tubing to 300'. Spot 25 sx cmt. (6 bbls) – ^{TOC at least 60' above surface shoe} _{-172'}
- ~~5.~~ PUH to 50'. Circ cmt to Surface w/5 sx.
6. Place Dry hole marker & weld a plate over csg w/well name.
7. Reclaim all surfaces & reseed.

3- MV plug 4120-4020 ~~33~~
4- Chacra plug 3430-3330
5- Pictured Cliffs plug 2685-2485
6- Fruitland plug 2400-2300
7- Kirtland plug 2180-2080

Canyon Largo Unit #335

Current

Devil's Fork

32 - 25N - 6W Rio Arriba County, NM

1620' FNL and 1750' FWL

Today's Date: January 11, 2008

Spud: March 2, 1984

Completed: March 27, 1984

API: 30-039-23388

Tops:

Ojo Alamo @ 2020'

Kirkland @ 2130'

Pictured Cliffs @ 2535'


Point Lookout @ 4794'

Mancos @ 4995'

Gallup @ 5924'

Perfs One Foot Each:

5928', 5937', 5950',
5961', 5971', 5984',
6002', 6025', 6027',
6029', 6031', 6048',
6127', 6134', 6142',
6157', 6179', 6205',
6208', 6230', 6244',
6257'



KB: 6798'

8-5/8" 24# Csg set @ 222'
175 sx cement

TOC @ 1800'

2-3/8" tbg @ 5923'

PBTD 6304'

TD 6400'

4-12" 10.5# J-55 csg @ 6398'
w/1025 sx cmt. TOC 1800'

Canyon Largo Unit #335

Proposed
Devil's Fork

32 - 25N - 6W Rio Arriba County, NM
1620' FNL and 1750' FWL

KB: 6798'

Today's Date: January 11, 2008

Spud: March 2, 1984

Completed: March 27, 1984

API: 30-039-23388

Tops:

Ojo Alamo @ 2020'

Kirkland @ 2130'

Fruitland 2350

Pictured Cliffs @ 2535'

Chacra @ 3380

Point Lookout @ 4794'

Mancos @ 4995'

Gallup @ 5924'

Perfs One Foot Each:

5928', 5937', 5950',
5961', 5971', 5984',
6002', 6025', 6027',
6029', 6031', 6048',
6127', 6134', 6142',
6157', 6179', 6205',
6208', 6230', 6244',
6257'

Surface Plug - Circ cmt to surf w/5 sx cmt

8-5/8" 24# Csg set @ 222'

175 sx cement

300' Spot 25 sx cmt (6 bbls)

TOC to 172'

RIH w/wireline. Set CIBP @ 1900'. Spot 25 sx cmt,
Est TOC @ 1550'. (6 bbls) ✓

← TOC @ 1800'

*- Kirkland 2130 plug 2180-2080
- Fruitland 2350 plug 2400-2300
- PL 2535 - plug 2685-2485
- Chacra 3380 plug 3430-3330
- MV top 4020 plug 4120-4020*

CIBP @ 5900' Dump 20' cmt on plug
2-3/8" tbg @ 5923'

PBTD 6304'

TD 6400'

4-12" 10.5# J-55 csg @ 6398'
w/1025 sx cmt. TOC 1800'