

30-045-25139

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator Turner Production Company Location: Unit P Sec. 28 Twp 30 Rng 9

Name of Well/Wells or Pipeline Serviced Federal 28 # 1

Elevation 5848 <sup>KB</sup> Completion Date 11/17/82 Cathodic Protection Total Depth 400' Land Type\* F

Casing, Sizes, Types & Depths ~~9 5/8" surface casing, 32.3 #, H-40 to 238',~~  
~~7" intermediate casing to 2725', 20.0 #, K, 4 1/2 production casing to 7039', 11.6 # &~~  
~~10.5 # J-55, and 2 3/8 tubing to 6898', 4.7 #, J.~~

If Casing is cemented, show amounts & types used \_\_\_\_\_

~~190 sacks surface casing, 450 sacks intermediate casing, 2 stage Howco: 125 & 150 for~~  
~~production casing.~~

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. UNKNOWN

Depths gas encountered: None

Type & amount of coke breeze used: 4000# Metalurgical

Depths anodes placed: 280, 290, 300, 310, 320

Depths vent pipes placed: 400'

Vent pipe perforations: 200-400'

Remarks: 270' to 350' - sandy shale

350' to 400' - sand

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.

