

30-045-09331

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit 2 Sec. 21 Twp 30 Rng 11

Name of Well/Wells or Pipeline Serviced _____

Morris A#6

Elevation 5791 Completion Date 10/9/94 Total Depth 448' Land Type P

Casing Strings, Sizes, Types & Depths 10 1/8 Set 99' of 8" PVC casing.

NO GAS or Boulders, BUT WATER WAS ENCOUNTERED AT 55' DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 140', AND A MAJOR FRESH WATER VEIN AT 375'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 448' Depth.

Used 58 SACKS of Lotesco SW (5800#)

Depths anodes placed: 425', 416', 405', 395', 385', 375', 365', 355', 220', 195', 185', 170', 160', 150', + 140'.

Depths vent pipes placed: SURFACE TO 448'.

Vent pipe perforations: BOTTOM 320'.

Remarks: _____

RECEIVED
R
JAN 20 1995

OIL COR. DIV.
DIST. 9

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Free.
If Federal or Indian, add Lease Number.