

30-045-09726

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit F Sec. 11 Twp 30 Rng 11

Name of Well/Wells or Pipeline Serviced Current #1

Elevation 5600 Completion Date 6/18/94 Total Depth 393' Land Type F

Casing Strings, Sizes, Types & Depths 99' of 8" P.S.C.

If Casing Strings are cemented, show amounts & types used 14 sacks

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 125' AND MORE

FRESH WATER AT 250'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 393' DEPTH.

USED 98 SACKS OF ASBURY 218R (4900#)

Depths anodes placed: 365', 355', 330', 320', 310', 297', 289', 203', 195', 187', 179', 171', 163', 147', + 139'.

Depths vent pipes placed: SURFACE TO 393'.

Vent pipe perforations: BOTTOM 270'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DEV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.