

30-045-09757

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit D Sec. 12 Twp 30 Rng 11

Name of Well/Wells. or Pipeline Serviced _____

Nye #13

Elevation _____ Completion Date 6/16/94 Total Depth 393' Land Type F

Casing Strings, Sizes, Types & Depths 6 1/2" SET 98' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 19 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

USED 15 SACKS OF CEMENT TO PLACE A 45' CEMENT PLUG. PLUG TO 115'

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 110', AND MORE FRESH

WATER AT 205'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: 320'-340'

Ground bed depth with type & amount of coke breeze used: 393' DEPTN.

USED 98 SACKS OF ASBURY 218R (4900#)

Depths anodes placed: 360', 352', 342', 330', 315', 300', 250', 238', 230', 215', 189', 175', 160', 150', & 140'

Depths vent pipes placed: SURFACE TO 393'

Vent pipe perforations: BOTTOM 270'

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.