

In Lieu of
Form 3160
(June 1990)

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

5 Lease Designation and Serial No.
NM-010910

6 If Indian, Allottee or Tribe Name

RCVD FEB 18 '08

7 If Unit or C.A. Agreement Designation
Cox Canyon Unit

8 Well Name and No.
Cox Canyon #009C

9 API Well No
30-045-33851

10 Field and Pool, or Exploratory Area
BLANCO MV/BASIN DK

11 County or Parish, State
San Juan, New Mexico

SUBMIT IN TRIPPLICATE

RECEIVED

FEB 13 2008

Bureau of Land Management
Farmington Field Office

1. Type of Well
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
WILLIAMS PRODUCTION COMPANY

3. Address and Telephone No
PO Box 640 Aztec, NM 87410-0640

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1980 FNL & 1905 FWL, Sec 20, T32N, R11W

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

Notice of Intent

☒ Subsequent Report

Final Abandonment

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

☒ Other Intermediate Casing

Change of Plans

New Construction

Non-Routine Fracturing

Water Shut-Off

Conversion to Injection

Dispose Water

(Note. Report results of multiple completion on Well Completion or Recombination Report and Log form)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)*

2/6/08-2/10/08

Drill 9-7/8" intermediate hole

2/11/08

TD 9-7/8" intermediate hole @ 2875'

Run 62 JT 7-5/8, 26 4 #, k-55, LT&C, Set @ 2860 GUIDE SHOE @ 2860, FLOAT @ 2811"

CEMENT 7.5/8" INTERMEDIATE CSG. @ 2860' SHOE DEPTH / 7-5/8" CASING CEMENTED ON 2/11/2008 @ 23:00

2 SLURRY CEMENT JOB / 20 BBLs. WATER SPACER / LEAD = 625 SXS PREMIUM LIGHT CMT + 8% + CaCl-2 + .25#/SX

CELLO FLAKE+119 BBLs. WATER=163 BBL OF SLURRY@12.1PPG=1319CuFt(YIELD+2.1/WGPS=15)TAIL=100SXS TYPE 3

CMT+1% CaCl-2+.25#/SX CELLO FLAKE+8.34BBLs. WATER=11 51BBLs. SLURRY@14.5 PPG=140 CuFt(YIELD=1 4/WGPS=

6 80) / DISPLACE WITH 132.5 BBLs. WATER / BUMP PLUG@ 1530 PSI-PLUG DOWN ON 2/12/2008@ 01:00 am / CHECK FLOAT

GOOD HOLD / PRESSURE UP TO 500 PSI AND SHUT IN / CIRCULATE 40 BBL'S OF CEMENT TO SURFACE. ✓

2/12/08

TEST PIPE RAM'S AND CASING TO 250 LOW FOR 10 MIN AND 1500 HIGH FOR 30 MIN EVERY THING TESTED OUT GOOD. ✓

ACCEPTED FOR RECORD

FEB 14 2008

FARMINGTON FIELD OFFICE
BY T. Sayers

14. I hereby certify that the foregoing is true and correct

Signed

Larry Higgins

Title Drilling C.O.M.

Date February 13, 2008

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOC