

409 - 30-039-24865
212 - 30-039-20843

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit NE Sec. 18 Twp 28 Rng 6

Name of Well/Wells or Pipeline Serviced San Juan 30-6 Unit No. 409
and No. 212 Wells.

Elevation ? Completion Date 11-21-90 Total Depth 475' Land Type P

Casing Strings, Sizes, Types & Depths 8" dia, PVC, to a depth of
20' below grade.

If Casing Strings are cemented, show amounts & types used 5 each 90 lb.
bags of Sackrete.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NA = None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Wet streak at 210' depth, $\leq$ 5' thick,
Muddy - Fresh Water.

Depths gas encountered: None = NA

Ground bed depth with type & amount of coke breeze used: 475' Deep with
99.9% Carbon coke breeze (Loresco SWB) = 4,700 lbs.

Depths anodes placed: 260', 340', 350', 360', 415', 425', 435', 445', 455', 465'.

Depths vent pipes placed: 0' to 475' deep.

Vent pipe perforations: From 220' to 475' deep

Remarks: _____

RECEIVED

NOV 30 1990

OIL CON. DIV
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.