

6-30-045-06657

1E-30-045-24849

2696W DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit I Sec. 10 Twp 27 Rng 12

Name of Well/Wells or Pipeline Serviced _____

THOMPSON C#6 AND CARTER Com Fed. #1E

Elevation _____ Completion Date 5/25/94 Total Depth 460' Land Type I

Casing Strings, Sizes, Types & Depths 5/22 Set 99' of 8" PVC Casing.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 18 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 130', AND A MAJOR

FRESH WATER VEIN AT 305'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 460' DEPTH.

USED 151 SACKS OF ASBURY 218R (7550#)

Depths anodes placed: 445', 438', 431', 424', 417', 410', 401', 263', 255', 200', 158', 151', 144', 137', + 130'.

Depths vent pipes placed: SURFACE TO 460'.

Vent pipe perforations: BOTTOM 340'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.