

3 - 30-045-13240  
26 - 30-045-25683

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS.  
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit M Sec. 07 Twp 28 Rng 09

Name of Well/Wells or Pipeline Serviced \_\_\_\_\_

Reid #3 And #26

Elevation \_\_\_\_\_ Completion Date 5/10/94 Total Depth 415' Land Type F

Casing Strings, Sizes, Types & Depths 5/8/94 Set 99' of 8" PVC Casing

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used.

NONE

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 140', AND MORE FRESH WATER AT 270'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 415' DEPTH.

USED 110 SACKS OF ASBURY 218R (5500#)

Depths anodes placed: 395', 385', 365', 355', 345', 335', 325', 290', 235', 210', 200', 190', 180', 170', + 160'.

Depths vent pipes placed: SURFACE TO 415'.

Vent pipe perforations: BOTTOM 290'.

Remarks: \_\_\_\_\_

RECEIVED  
JAN 20 1995

OIL CON. DIV.  
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.