

2636W

B 6-30-045-05938

B 9-30-045-05943

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc Location: Unit G Sec. 07 Twp 26 Rng 08

Name of Well/Wells or Pipeline Serviced _____

Newsom B#6 AND B#9

Elevation 6219 Completion Date 4/20/94 Total Depth 392' Land Type F

Casing Strings, Sizes, Types & Depths 4 1/2" SET 99' OF 8" PVC CASING.

NO GAS OR WATER, BUT 5' (60'-65') OF BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 21 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. NIT FRESH WATER AT 115', AND MORE FRESH

WATER AT 330'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 392' DEPTH

USED 51 SACKS OF LOIESCO SW (5100#)

Depths anodes placed: 375', 367', 352', 344', 325', 315', 305', 295', 285', 258', 250', 239', 231', 197', + 183'.

Depths vent pipes placed: SURFACE TO 392'

Vent pipe perforations: BOTTOM 275'

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.