

1- 30-045-07869

8- 30-045-21564

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit 4 Sec. 28 Twp 29 Rng 9

Name of Well/Wells. or Pipeline Serviced _____

Grubbing #1 AND #8

Elevation 5646 Completion Date 5/17/94 Total Depth 407 Land Type F

Casing Strings, Sizes, Types & Depths 5/8" 99' of 8" PVC surface

CASING. WATER AT 60', NO GAS OR BOULDERS. DURING CASING.

If Casing Strings are cemented, show amounts & types used 20 BAGS

CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Placed A 30' Cement Plug (105'-75'). Used 10 SACKS OF CEMENT.

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. 1st WATER AT 60'. MORE FRESH WATER AT 125',

AND 270'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 407' Depth.

Used 107 SACKS OF ASBURY 218R (5350#)

Depths anodes placed: 395', 385', 375', 365', 235', 225', 215', 205', 195', 185', 175', 165', 157', 143', + 135'.

Depths vent pipes placed: SURFACE TO 407'.

Vent pipe perforations: BOTTOM 285'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.