

1 - 30-045-10340
6 - 30-045-20439

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit H Sec. 30 Twp 31 Rng 10

Name of Well/Wells or Pipeline Serviced _____

Pierce #1 And #6

Elevation _____ Completion Date 8/16/94 Total Depth 354' Land Type F

Casing Strings, Sizes, Types & Depths 8/4 Set 99' of 8" PVC Casing.

NO GAS OR WATER, BUT 12' (45'-57') of Boulders were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Used 5 SACKS Cement, To Place A 15' (100'-115') Plug, To Stop WATER, AND A SLIGHT AMOUNT OF GAS

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 260', AND MORE FRESH

WATER AT 350'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: 350'

Ground bed depth with type & amount of coke breeze used: 354' Depth.

Used 58 SACKS OF Asbury 218R, AND 13 SACKS OF Lotesco SW (4200#)

Depths anodes placed: 335', 327', 319', 311', 303', 295', 287', 279', 271', 236', 228', 220', 190', 155', + 145'.

Depths vent pipes placed: SURFACE TO 354'.

Vent pipe perforations: BOTTOM 220'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.