

210 - 30-045-29065

112 - 30-045-29026

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit G Sec. 07 Twp 30 Rng 10

Name of Well/Wells. or Pipeline Serviced _____

SULLIVAN #210 AND #1R

Elevation 6174 Completion Date 6/15/94 Total Depth 411' Land Type F

Casing Strings, Sizes, Types & Depths 6 1/4" SET 99' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 105' AND MORE

FRESH WATER AT 195'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 411' Depth.

USED 104 SACKS OF ASBURY 218R (5200#)

Depths anodes placed: 380', 368', 350', 340', 330', 320', 270', 260', 250', 240', 230', 220', 210', 200', +155'.

Depths vent pipes placed: SURFACE TO 411'.

Vent pipe perforations: BOTTOM 290'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.