

2A-30-045-22526

6-30-045-21050

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit F Sec. 13 Twp 30 Rng 10

Name of Well/Wells. or Pipeline Serviced _____

Turner Fed. #2A And #6

Elevation 6524 Completion Date 6/22/94 Total Depth 456' Land Type F

Casing Strings, Sizes, Types & Depths 6/19 Set 98' of 8" PVC Casing.

No Gas, Water, or Boulders Were Encountered During Casing.

If Casing Strings are cemented, show amounts & types used Cemented
WITH 17 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 115', AND MORE FRESH
WATER AT 325'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 456' Depth.
Used 120 SACKS OF ASBURY 218R (6000#)

Depths anodes placed: 445', 438', 431', 424', 417', 410', 403', 396', 386', 376', 226', 219', 212', 205', + 198'.

Depths vent pipes placed: SURFACE TO 456'.

Vent pipe perforations: BOTTOM 340'.

Remarks: _____

RECEIVED
IN JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.