

5-30-045-09.753

16A-30-045-22861

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc Location: Unit C Sec. 12 Twp 30 Rng 11

Name of Well/Wells. or Pipeline Serviced _____

Nye #5 AND #16A

Elevation _____ Completion Date 6/17/94 Total Depth 379' Land Type F

Casing Strings, Sizes, Types & Depths 6 1/4 SET 98' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Placed A 15' (100'-115') Cement Plug. Used 5 Sacks of Cement

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 105' AND MORE

FRESH WATER AT 330'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: 330' TO 335'

Ground bed depth with type & amount of coke breeze used: 379' Depth.

Used 93 SACKS OF ASBURY 218R (H650#)

Depths anodes placed: 320', 312', 304', 296', 288', 280', 272', 250', 242', 183', 175', 165', 155', 145', + 137'.

Depths vent pipes placed: SURFACE TO 379'.

Vent pipe perforations: BOTTOM 260'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.