

89-30-039-07177
52-30-039-07155

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 4 Twp 27 Rng 5

Name of Well/Wells or Pipeline Serviced SAN JUAN 27-5 UNIT #52, #89

cps 738w

Elevation 6619' Completion Date 4/14/66 Total Depth 320' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. WET AT 40' & 160'

Depths gas encountered: N/A

Type & amount of coke breeze used: 4750 lbs.

Depths anodes placed: 280', 273', 267', 220', 211', 140', 130', 124', 118', 112'

Depths vent pipes placed: 280' OF 3/4" PLASTIC HOSE

Vent pipe perforations: 280'

Remarks: qb #1

RECEIVED
MAY 31 1994

DIV. I

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

43/4 D199

KLM #15-170

Date 4-14-66

Well Name: 5-14-27-5 #89 & 27-5 #52			CPS No. 738 W		
Location: SW 4-27-5			Work Order No. 189-54310-50-20		
Anode Hole Depth: 320	Total Drilling Rig Time: 16 Hrs	Type & Size Bit Used: 778 872663-320		No. Sacks Mud Used: 1	
No. Sacks Lost Circulation Mat'l Used: 0	Anode Depth:				
	#1 280	#2 273	#3 267	#4 220	#5 211
Total Lbs. Coke Used: 4750	Anode Output (Volts):				
	#1 3.6	#2 3.9	#3 4.5	#4 3.0	#5 3.0
Total Circuit Resistance:	No. Ft. Surface Cable Conduit:				
Volts 11.3	Amps 11.3	Ohms 1.02	2175 on Anodes -		

Drilling Log (Attach Hereto). ☐

7	130	8	124	9	118	10	112
7	4.0	8	4.6	9	5.4	10	5.0

Remarks:

Static R/Gs 600' S 52 = .76 #89 = 600' N = .69

3/4" Plastic Hose to No. 1 Anode - Perforated opposite Each Anode

15 lbs Chemical to G.B.

Good All Rectifier 30-20 - 2NEG Ser. #65C6691

2175'
416
2591 TOTAL #8 WIRE

All Construction Completed

Arrele
(Signature)

GROUND BED LAYOUT SKETCH



