

1497

13 - 30-045-07629

15 - 30-045-07619

20 - 30-045-23708

33 - 30-045-25505

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL INC. Location: Unit N Sec. 33 Twp 29 Rng 10

Name of Well/Wells or Pipeline Serviced ZACHERY #13, #15, #20, #33

cps 6339w

Elevation N/A Completion Date 9/6/83 Total Depth 220' Land Type* N/A

Casing, Sizes, Types & Depths 40'

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 40' & 120'

Depths gas encountered: N/A

Type & amount of coke breeze used: 1650 lbs.

Depths anodes placed: 201', 200', 190', 180', 170', 160', 150', 135', 120', 110'

Depths vent pipes placed: 200'

Vent pipe perforations: N/A

Remarks: cg#2

RECEIVED
MAY 31 1991

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CORROSION CONTROL CO.

P. O. BOX 179 - PHONE 334-6361
AZTEC, NEW MEXICO 87410

#13, #15, #33

Drilling Log (Attach Hereto). ☐

6339W

Completion Date 9-6-83

Well Name <i>Anchor 18-1 Unit 20</i>		Location <i>U.T.P.C.</i>		N 33 29 10	
Type & Size Bit Used				Work Order No.	
Anode Hole Depth <i>220'</i>	Total Drilling Rig Time	Total Lbs. Coke Used <i>1650#</i>	Lost Circulation Mat'l Used	No. Sacks Mud Used	
Anode Depth					
#1 <i>210</i>	#2 <i>200</i>	#3 <i>190</i>	#4 <i>180</i>	#5 <i>170</i>	#6 <i>160</i>
#7 <i>150</i>	#8 <i>135</i>	#9 <i>120</i>	#10 <i>110</i>		
Anode Output (Amps)					
#1 <i>3.4</i>	#2 <i>3.8</i>	#3 <i>3.6</i>	#4 <i>5.0</i>	#5 <i>4.1</i>	#6 <i>3.7</i>
#7 <i>4.4</i>	#8 <i>3.0</i>	#9 <i>2.7</i>	#10 <i>3.1</i>		
Anode Depth					
#11	#12	#13	#14	#15	#16
#17	#18	#19	#20		
Anode Output (Amps)					
#11	#12	#13	#14	#15	#16
#17	#18	#19	#20		
Total Circuit Resistance			No. 8 C.P. Cable Used		
Volts <i>12.0</i>	Amps <i>17.8</i>	Ohms <i>.67</i>	<i>1325'</i>		No. 2 C.P. Cable Used

Remarks: *Set 40' CASING WATER WAS AT 40' & 120' USED 20' VERT PIPE.*

All Construction Completed

(Signature)

GROUND BED LAYOUT SKETCH

