UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
LEASE DESIGNATION AND SERIAL NO.

OLOGICAL	SURVEY	SF	07

GEOLOGICAL SURVEY			SF 079051		
	ORY NOTICES AND REPORT OF PROPERTY OF THE PROP		6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
OIL GAS WELL WELL	X OTHER		7. UNIT AGREEMENT NAME San Juan 28-6 Unit		
2. NAME OF OPERATOR	N.	1031 20 4270	8. FARM OR LEASE NAME		
	ural Gas Company JAN 29 1973		San Juan 28-6 Unit		
3. ADDRESS OF OPERATOR	أشا		, · •		
PO Box 990,	Farmington, NM 87401Comport location clearly and in accordance	with any State requirements.	132 10. FIELD AND POOL, OR WILDCAT		
See also space 17 belo At surface	See also space II delow.)		Basin Dakota		
	•		Sec. 32, T-28-N, R-6-W		
14. PERMIT NO.	15. ELEVATIONS (Show v	whether DF. RT. GR. etc.)	12. COUNTY OR PARISH; 13. STATE		
11. Ibaciii no.	10. 12. 11. 10. 10. 10. 10. 10. 10. 10. 10. 10	6462'GL	Rio Arriba New Mexico		

16.	Check Appropriate Box to Inc	licate Nature of Notice, Report, o	or Other Data		
N	OTICE OF INTENTION TO:	SUB	SEQUENT REPORT OF:		
TEST WATER SHUT-OF	F PULL OR ALTER CASING	WATER SHUT-OFF	X REPAIRING WELL		
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	X ALTERING CASING		
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*		
REPAIR WELL	CHANGE PLANS	(Other) (NOTE: Report res	sults of multiple completion on Well		
(Other) 17. DESCRIBE PROPOSED OR proposed work. If nent to this work.)*	COMPLETED OPERATIONS (Clearly state al well is directionally drilled, give subsur		ompletion Report and Log form.) ates, including estimated date of starting any retical depths for all markers and zones perti-		
,	TTD 04651 D 105	. 70 004 tzg ·	0.4551		
12-6-72	TD 3465'. Ran 105 joints 7", 20#, KS intermediate casing, 3455', set at 3465'. Cemented with 232 cu.ft. cement, WOC 12 hours, held 1200#/30 min. Top of cement at 2400'.				
12 - 11-72	TD 7655'. Ran 239 joints 4 1/2", 11.6 and 10.5#, KS and KE production casing, 7643' set at 7655'. Float collar at 7646'. Cemented with 642 cu.ft. cement. WOC 18 hours. Top of cement at 2950'.				
1-15-73	7556-71', 7613-28' with	18 shots per zone. Frac'	45-50', 7460-70', 7528-33', d with 60,000# 40/60 sand ets of 18 balls each. Flushed		
	· · · · · · · · · · · · · · · · · · ·	RECEIVE			
		JAN 21 19	. //		
		OIL CON. CO	יוכטע		
18. I hereby derrify that	the foregoing is true and correct	DIST. 3	<i>f</i>		
signed #10	V00 X TIT	LE Petroleum Engineer	DATE January 17, 1973		
(This space for Federal APPROVED BY	ral or State office use)	LE	DECEIVED.		
CONDITIONS OF AF			IAN 1 9 1973		

*See Instructions on Reverse Side

U. S. GEOLOGICAL SUKVEY DURANGO, COLO.