



(SUBMIT IN TRIPLICATE)

Land Office New Mexico
Lease No. 03541
Unit Bancroft

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 6, 1958

Well No. 2 is located 1650 ft. from N line and 800 ft. from E line of sec. 29

Sec. 29
(¼ Sec. and Sec. No.)

29N
(Twp.)

9N
(Range)

H.M.P.M.
(Meridian)

Blanco H.V. Antec P.C.
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 5925 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

May 4, 1958. Total Depth 3851'.

Ran 93 joints 7 5/8", 26.40#, J-55 casing (3839') set at 3851'. Two stage cementing tool set at 2193'. First stage 50 sacks regular cement, 50 sacks Pozmix with 2% Gel and 1/4# Floccul/sk, followed by 50 sacks regular cement with 2% CaCl. Second stage 75 sacks regular cement, 75 sacks Pozmix with 2% Gel.

Held 1800# for 30 minutes.

Top of cement by temperature survey at 1600'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By Original Signed F. H. WOOD

Title Petroleum Engineer