

# 330 30-039-25522

# 53 30-039-07158

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit M Sec. 05 Twp 27 Rng 05

Name of Well/Wells or Pipeline Serviced \_\_\_\_\_

S. J. 27-5 #330 AND #53

Elevation \_\_\_\_\_ Completion Date 12/2/95 Total Depth 412' Land Type P

Casing Strings, Sizes, Types & Depths 12 1/2" SET 100' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 220'.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 412' DEPTH.

Used 102 SACKS OF ASBURY 218R (5100#)

Depths anodes placed: 375', 365', 355', 345', 335', 325', 315', 307', 250', 240', 230', 180', 160', 150', + 140'

Depths vent pipes placed: SURFACE TO 412'.

Vent pipe perforations: BOTTOM 280'.

Remarks: \_\_\_\_\_

RECEIVED  
JAN 11 1996

OIL CON. DIV.  
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.