

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
OMB No. 1004-0135
Expires July 31, 1996

SUNDRY NOTICES AND REPORTS ON WELLS

APR 21 2008

Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

NM-12233

6. If Indian, Allottee or Tribe Name

Kingston Field Office

7. If Unit or CA/Agreement, Name and/or N

SUBMIT IN TRIPLICATE - Other instructions on reverse side

1.

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Elm Ridge Exploration Company, LLC

3a. Address

PO Box 156 Bloomfield, NM 87413

3b. Phone No. (include area code)

505-632-3476

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 26-T24N-R8W

830' FNL X 670' FEL

8. Well Name and No.

S. Blanco Federal 26-6

9. API Well No.

30-045-25217

10. Field and Pool, or Exploratory Area

Lybrook Gallup Ext.

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize <input type="checkbox"/> Deepen <input type="checkbox"/> Production (Start/Resume) <input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing <input type="checkbox"/> Fracture Treat <input type="checkbox"/> Reclamation <input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair <input type="checkbox"/> New Construction <input type="checkbox"/> Recomplete <input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans <input checked="" type="checkbox"/> Plug and Abandon <input type="checkbox"/> Temporarily Abandon
	<input type="checkbox"/> Convert to Injection <input type="checkbox"/> Plug Back <input type="checkbox"/> Water Disposal

13. Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

This well is incapable of production. Elm Ridge Exploration requests approval to plug and abandon this well according to the attached procedure.

RCVD APR 24 '08

OIL CONS. DIV.

DIST. 3

14. I hereby certify that the foregoing is true and correct

Name (Printed/Typed)

Amy Mackey

Title

Production Assistant

Signature

Date

April 16, 2008

THIS SPACE FOR FEDERAL OR STATE USE

Approved by

Original Signed: Stephen Mason

Title

Date

APR 23 2008

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on reverse)

NMOCD

Plugging Program for South Blanco Federal 26-6:

- 1: Set 4-1/2" cement retainer at 5322'. Squeeze below retainer with 8 sacks to cover perfs. Spot 8 sacks on top of retainer to cover 50' over top of Gallup inside casing. PU and reverse circulate with 2 tubing volumes of water.
- 2: PU to 3510' Spot 12 sx balanced plug from ^{2794'} ~~3510'~~ to ^{2694'} ~~3410'~~ to cover top of Cliff House inside casing. PU and reverse circulate with 2 tubing volumes of water.
- 3: PU to 2415'. Spot 93 sx balanced plug from 2415' to 1241', to cover tops of Chacra (as required by NMOCD), Pictured Cliffs, Fruitland, and Ojo Alamo inside casing. PU and reverse circulate with 2 tubing volumes of water. TOOH.
- 4: PU to 329'. Pump 25 sx or sufficient volume to bring cement to surface inside casing.
- 5: Remediate location per conditions of approval.

Elm Ridge Resources

Pertinent Data Sheet

Well Name: South Blanco Federal 26 #6
Footage: 830' FNL and 670' FEL
Location: Section 26, T24N, R8W
County: San Juan County, NM
API#: 30-045-25217

Field: Lybrook Gallup Ext.

Elevation: 6880' KB

TD: 5700' KB

PBTD: 5652' KB

Completed: 8/22/82

Casing Record:

Hole Size	Casing Size	Wt.	Grade	Depth Set	Cement
12-1/4"	8-5/8"	24#	K-55	229'	200 sx (Circ. To Surface)
7-7/8"	4-1/2"	10.5#	K-55	5691'	Stg 1: 600 sx Stg 2: 500 sx (DV@3086') ⁽¹⁾

⁽¹⁾ 1st Stage: TOC at 3369' (calc.). 2nd Stage: TOC: Circulated cement to surface

Tubing Record: None

Rod Record: None

Formation Tops:

Nacimiento	Surface
Ojo Alamo	1291'
Kirtland-Fruitland	1403'
Pictured Cliffs	1940'
Lewis	2036'
Chacra	2365'
Cliff House	3460'
Menefee	3496'
Point Lookout	4260'
Mancos	4463'
Gallup	5322'

Perforations: Gallup: 5377-5599'

Wellbore Diagram

South Blanco Federal 26-6

NE/4 Sec. 26, T24N, R8W

San Juan County Co., NM

API #30-045-25217

Before

Nacimiento-Surface

12-1/4" OH
8-5/8" 24# K-55 set @ 229'
Circulated cmt to surface

TOC: Circulated to surface

Ojo Alamo 1291'
Kirtland-Fruitland 1403'

Pictured Cliffs 1940'
Lewis 2036'

Chacra 2365'

4-1/2" DV Tool @ 3086'

TOC: 3369'

Cliff House 3460'
Menefee 3496'

Point Lookout 4260'

Mancos 4463'

Gallup 5322'

Gallup Perfs: 5377-5599'

PBTD: 5652'
4-1/2" 10.5# K-55 set @ 5691'
TD: 5700'

S. Blanco Federal 26-6WBD
4/16/2008

Wellbore Diagram

South Blanco Federal 26-6
NE/4 Sec. 26, T24N, R8W
San Juan County Co., NM
API #30-045-25217
After

Nacimiento-Surface



12-1/4" OH
8-5/8" 24# K-55 set @ 229'
Circulated cmt to surface

Plug 4

Ojo Alamo 1291'
Kirtland-Fruitland 1403'

Plug 3

Pictured Cliffs 1940'
Lewis 2036'

Chacra 2365'

4-1/2" DV Tool @ 3086'

TOC: 3369'

Cliff House 3460'
Menefee 3496'

Plug 2

Point Lookout 4260'

Mancos 4463'

Gallup 5322'

Plug 1
Gallup Perfs: 5377-5599'

PBTD: 5652'
4-1/2" 10.5# K-55 set @ 5691'
TD: 5700'

S. Blanco Federal 26-6WBD
4/16/2008

**UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
FARMINGTON DISTRICT OFFICE
1235 LA PLATA HIGHWAY
FARMINGTON, NEW MEXICO 87401**

Attachment to notice of
Intention to Abandon:

Re: Permanent Abandonment
Well: 6 South Blanco Federal 26

CONDITIONS OF APPROVAL

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
2. Farmington Office is to be notified at least 24 hours before the plugging operations commence (505) 599-8907.
3. The following modifications to your plugging program are to be made:
 - a) Place the Mesaverde plug from 2794' – 2694'.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.