

160-30-039-06954 242-30-039-24480

82-30-039-06946 173-30-039-06941

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Union Oil Company of California Location: Unit Sec. 23 Twp 27N Rng 6WName of Well/Wells or Pipeline Serviced Rincon #160 PC Rincon #82 MVRincon #242 FC Rincon #713 DKElevation 6610' Completion Date 11/19/65 Total Depth 320' Land Type* FCasing, Sizes, Types & Depths NoneIf Casing is cemented, show amounts & types used None

If Cement or Bentonite Plugs have been placed, show depths & amounts used

None

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 40' 105'-115' 10'thickDepths gas encountered: NAType & amount of coke breeze used: Type unknown 4200 lbsDepths anodes placed: 154' to 240'Depths vent pipes placed: 182'Vent pipe perforations: ?Remarks: El Paso Natural Gas was the operator when this ground bed was installedFirst ground bed installed on this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED

MAY 09 1990

OIL CON. DIV.

DIST. 3

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

18

Date 11-19-65

Well Name Rincon #160 #82 & #173		CPS No. 701W	
Location SW 23-27-6		Work Order No. 54163 184. 52831-50-20	
Anode Hole Depth 320	Total Drilling Rig Time 17 Hrs	Type & Size Bit Used 7 7/8 - 39 11/16 = 320	
No. Sacks Lost Circulation Mat'l Used 0	No. Sacks Mud Used 0		
Anode Depth		Anode Output (Volts)	
#1 190	#2 234	#3 228	#4 222
#5 203	#6 197	#7 5.3	#8 5.5
#9 4.9	#10 4.3	#11 4.5	#12 5.0
Total Lbs. Coke Used 4200		No. Ft. Surface Cable Conduit 2282'	
Total Circuit Resistance Volts 11.1 Amps 12.9 Ohms 0.86			

Drilling Log (Attach Hereto). ☐

Remarks: Static R's 650 SW #160 = .74, 600' S #173 = .72
600' W of 82 = .74, 4 lbs Chemical to G/B
3/4" Plastic Hose to #10 Anode = 182'
Install Good All Rectifier 45V30A (4 NEG) Ser. 65C 6634

All Construction Completed

Amels
(Signature)

GROUND BED LAYOUT SKETCH



