DEPARTMENT OF THE INTERIOR OF COMMENT IN TRIPLICATE STATES BUREAU OF LAND MANAGEMENT SUNDRY NOTICES AND REPORTS ON WELLS 100 and use this form for geographic and the production of the produ				Form approved.	
SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for personal to east or in detered or pints then to a different reservoir.) Sunday or state of the control of the contr	'Form 3160-5 November 1983)		(O+b-= 1==+=++++++++++++++++++++++++++++++++	Expires August	31, 1985
SUNDRY NOTICES AND REPORTS ON WELLS (1) For the control for proposed to be given deprete of sold back to a different reservoir. (2) The control for proposed to be given deprete of sold back to a different reservoir. (3) C S - 089-07000 (4) The control of th					
SUND Y NOTICES AND REPORTS ON WELLS The form to proposal to sold service or observed to the former reserved. Out O	BUREA	U OF LAND MANAGEMENT	· · · · · · · · · · · · · · · · · · ·		
136 30 30 30 30 30 30 30				O. IF INDIAN, ALLOTTE	E OR TRIBE NAME
136 30 30 30 30 30 30 30	(Do not use this form for propo- Use "APPLICA"	sals to drill or to deepen or plug bac ATION FOR PERMIT—" for such pro-	ck to a different reservoir.	N/A	
THE PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeze. A Drivent Process of the process	1			<u> </u>	/AE
2. NAME OF OPERATOR Union Old Company of California dba UNOCAL 3. ADDRESS OF OPERATOR UNION OLD COMPANY OF CALIFORNIA DRAW MEXICO 87413 4. DOCUMENT OF THE STATE AND PALL RICHARD UNIT 136E - 1175' FNL + 830 FML Rincon Unit 136E - 1175' FNL + 830 FML Rincon Unit 63 - 990' FNL + 890 FML 14. PERMIT NO. 15. LEAVATORS 1809 WERE PART OF THE PA		130	- (2)	Rincon Unit	t
Union Oil Company of California das UNOCAL A section of official of New Mexico 87413 P.O. Box 850, Bloomfield, New Mexico 87413 P.O. Box 850, Bloomfiel	2. NAME OF OPERATOR		30-039-070/0	8. FARM OR LEASE NAT	K.S.
P.O. Box 850, Bloomfield, New Mexico 87413 1. Decretion of the flower in the control of the con		California dba UNOCA	L , J	Rincon Uni	t
Rincon Unit 136E - 1175' FNL + 830 FNL Rincon Unit 136E - 1175' FNL + 830 FNL Rincon Unit 136E - 1175' FNL + 830 FNL Rincon Unit 136E - 1175' FNL + 830 FNL Rincon Unit 63 - 990' FNL + 890 FNL 16. LEXAMBONS (Show watcher DIC CON. DIV 12 COUNTY OF PARLES 13 LEVEL 14 COUNTY OF PARLES 14 LEVEL 15 L				9. WBLL NO.	
Rincon Unit 136E - 1175' FNL + 830 FNL Rincon Unit 63 - 990' FNL + 890 FNL Rincon Unit 63 - 990' FNL + 890 FNL Rincon Unit 63 - 990' FNL + 890 FNL 16. BLEVATIONS (Show whether DF) 16. Check Appropriate Box To Indicate Native of Notice, Report, or Other Data Source or Investions To: Test water 8807-orr FRIC AFTIDA NOTICE OF INVESTIONS TO: TEST WATER 8807-OFF FRICTURE TRADET ARMONOUS ALTER CASINO REPAIR WELL (Other) Install Cathodic Protection (O	P.O. Box 850, Bloomfi	eld, New Mexico 87413			
Rincon Unit 136E - 1175' FNL + 830 FNL Rincon Unit 63 - 990' FNL + 890 FNL Rincon Unit 63 - 990' FNL + 890 FNL Rincon Unit 63 - 990' FNL + 890 FNL 16. BLEVATIONS (Show whether DF) 16. Check Appropriate Box To Indicate Native of Notice, Report, or Other Data Source or Investions To: Test water 8807-orr FRIC AFTIDA NOTICE OF INVESTIONS TO: TEST WATER 8807-OFF FRICTURE TRADET ARMONOUS ALTER CASINO REPAIR WELL (Other) Install Cathodic Protection (O	See also space 17 below.)	nearly and in accordance with adver-	FFVF	Blanco MV/_Ba	asin DK
Rincon Unit 63 - 990' FRL + 890 FRL Rincon Unit 63 - 990' FRL + 890 FRL 11. PERMIT NO. 12. Sec. 23, T27N, R7W 13. Sec. 23, T27N, R7W 14. PERMIT NO. 15. SEC. 26, T27N, R7W 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Notice of Intention To: TEST WATER SECTOR PLANT PLANT PLANT PLANTS SHOOT OR ACTORING THE SHOOT OF INTENTION TO: TEST WATER SECTOR PLANT PLANT PLANTS SHOOT OR ACTORING TRACTURE TREAT SHOOT OR ACTORING THE TREAT SHOOT OF INTENTION TO: TEST WATER SECTOR THE SHOOT PLANTS SHOOT OR ACTORING TRACTURE TREAT SHOOT OR ACTORING THE COMPLETE SHOOT OR ACTORING THE SHOOT PLANTS SHOOT OR ACTORING TRACTURE TREAT SHOOT OR ACTORING THE SHOOT PLANTS SHOOT OR ACTORING TRACTURE TREATMENT SHOOT OR ACTORING TRACTURE TREATMENT SHOOT OR ACTORING THE SHOOT PLANTS SHOOT OR ACTORING THE SHOOT OR ACT		# 47 / 5			RLK. AND
Sec. 23, 127N, R7W 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Notice of Intention To: State Marks Sector of Intention To: State Water Sector of Only Intention To: State Water Sector of Only Intention To: State Water Sector of Intention To: State Water Sector of Only Intention To: State Water Sector of Intention To: State Water Sector of Only Intention To:			66T9 9 1002	SURVEY OR ARMA	
Check Appropriate Box To Indicate Nature of Molice, Report, or Other Data Check Appropriate Box To Indicate Nature of Molice, Report, or Other Data NOTICE OF INTERTION TO: TEST WATER SHOTOFF PRACTURE TREAT SHOOT OR ACIDITE REPAIR WILL CHANGE PLANS (Other) Install Cathodic Protection Uses the monostic or constanting of Random Value and proper treated dates. Includes estimated date of iterting and measured and true vertical depths for all markers and tones performent to the world. Proposed installation of Cathodic Protection to well casing: PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeze (99.55 carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze. A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existin roads and locations. See attached map. UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE AREA OCT 14 1992 ACCEPTED FOR RECORD OCT 14 1992 FARMINGTON RESOURCE AREA FARMINGTON RESOURC	Rincon Unit 63 - 99	0 FNL + 890 FWL	UC & & 1998	Sec. 23, T27N	. R7W
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: TEST WATES SHOT-OFF PRACTURE TREAT SHOOT OA ACIDIE SEPAINS CASHNO MULTIPLE COMPLETE SHOP ON ACIDIES SHOP ON ACIDIES SHOP OF SHORT OF SHOR	14. PERMIT NO.	15. ELEVATIONS (Show whether DF)	DIR CON DIV		
Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data Notice of Intention to: TEST WITES SHOT-OFF PRACTURE TREAT SHOOT OR ACIDIER SHOT OR ACIDIER SHOOT OR ACIDIER SHOUT OR ACIDIER SHOOT OR ACIDIER SHOUT OR		6605 GR, 6736 DF		Rio Arriba	NM
TEST WATER SHUT-OFF PCLL OR ALTER CASINO MULTIPLE COMPLETE SHORT OF: TEST WATER SHUT-OFF PCLL OR ALTER CASINO MULTIPLE COMPLETE SHORT OF ACIDITE SHOOT OR ACIDITE ADAPBON' CHANGE PLANS (Other) Install Cathodic Protection Other) Install Cathodic Protection Install Cathodic Protection Other) Install Cathodic Protection Other Recompletion on Medication and Installed Protection Other Protection Installed On Existing Well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existing the protection of the protection Install Cathodic Protection Install Cathodic Protection Install Cathodic Prot	6. Charle A			4h D4-	
TEST WATER SBUT-OFF PRACTURE TREAT SHOOT OR ACIDITE SEPARE TO THE TREAT SHOOT OR ACIDITE ASAROM. MULTIPLE COMPLETE SHOOT OR ACIDITE SHOOT OR COMPLETE OR PREATMENT (Chemity State all) perfinent details, and give perfinent dates, including settingted date of starting and short or vertical depths for all markers and some performent to this work. PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeae (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze. A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existin roads and locations. See attached map. UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE AREA TO SEE STATE TITLE (Temp.) Production Tech PATE TITLE TITLE THE SHOT OF TECHNIC OF STATE SHOWS SEED TO SEE STATE STA					
PRACTURE TREAT SHOOT OR ACIDISE (Other) Install Cathodic Protection (Other) Install Cathodic Protection (Other) Install Cathodic Protection (Other) Install Cathodic Protection (Note: Report results of multiple completion on Wall (Other) Install Cathodic Protection (Other) Install Cathodic Report table for all markers and some performed work. If will be directionally drilled give subsurface locations and measured and true vertical depths for all markers and sones performed with in the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeae (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze. A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existin roads and locations. See attached map. (OCT 14 1992	NOTICE OF INTER	ITION TO:	8088800	INT REPORT OF:	
SHOOT OR ACIDIER REPAIR WILL (Other) Install Cathodic Protection (Other) Install Cathodic Protection to well Proposed installation of Cathodic Protection to well casing: Proposed installation of Cathodic Protection to well casing: PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeae (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze. A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existin roads and locations. See attached map. UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE AREA TO BE TO			WATER SHUT-OFF	REPAIRING '	WELL
NEPAIR WELL (Other) Install Cathodic Protection (Other) Install Cathodic Protection for Recompletion seminated and true vertical depths for all markers and tone testing as and true vertical date of teating as and the protection (Other) Install Cathodic Protection to well casing: (Other) Install Cathodic Protection in Sully 1, 1993. (Other) Install Cathodic Protection and Install English and Install					[
Other) Install Cathodic Protection (Nors: Report results of multiple completion on Well Completion of Recoupleting Report and Log form.) 1 us a ribb required on Completion of Recoupleting Report and Log form.) 1 us a ribb required on Completion of Recoupleting Report and Log form.) 1 us a ribb required on Completion of Recoupleting Report and Log form.) 1 us a ribb required on Completion of Recoupleting Report and Log form.) 1 us a ribb required on Completion of Recoupleting Report and Log form.) 1 us a ribb report and Log form.) 2 us a ribb report and Log for a ribb report and Log form.) 2 us a ribb report and Log for a ribb report and Log form.) 2 us a ribb report and Log for a ribb report and Log form.) 2 us a ribb report and Log for a ribb report and Log form.) 2 us a ribb report and Log for a ribb report and Log form.) 2 us a				ABANDONME	MT
Proposed installation of Cathodic Protection to well casing: Proposed installation of Cathodic Protection to well casing: PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeae (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze. A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existing roads and locations. See attached map. UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE AREA OCT 14 1992 OCT 14 1992 OCT 14 1992 TITLE (Temp.) Production Tech DATE DATE DATE DATE PROVED BY TITLE TI	h		(NOTE: Report results	of multiple completion	on Well
Proposed installation of Cathodic Protection to well casing: PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeae (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze. A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existin roads and locations. See attached map. UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE AREA TO SEE THE PARTY OF TH					
PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeae (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze. A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existin roads and locations. See attached map. UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE ANEA TO BE THE ANALY OF	proposed work if well is direction	onally drilled, give subsurface location	ns and measured and true vertical	depths for all marker	s and sones perti
cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existin roads and locations. See attached map. UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE AREA OCT 14 1992 FARMINGTON NEW MEXICO FARMINGTON NEW MEXICO TITLE (Temp.) Production Tech DATE DATE DATE	PROCEDURE: Drill a 6 boundary. Ten Dur-Ir formation in favorabl carbon) to completely	diameter hole, 300' on anodes will be inst e locations. This wil surround the anodes.	deep within the existable deep within the upper the backfield with the control of	rmost water be coke breeae (9	aring 9.5%
UNOCAL's completion expectation is July 1, 1993. FARMINGTON RESOURCE AREA OCT 14 1992 BETT FARMINGTON NEW MEXICO FARMINGTON NEW MEXICO TITLE (Temp.) Production Tech DATE DATE DATE DATE DATE	cable will be connect the rectifier will al These cables will be	ed to the anode from t so be buried and conne buried 18" to 24" deep	the rectifier. Negat ected to well casings o (on previously dist	ive DC cables to be protect urbed ground)	from ed.
8. I bereby certify that the foregoing is true and correct Signed Landburg Title (Temp.) Production Tech APPROVED BY TITLE DATE DATE DATE	UNOCAL's completion e	expectation is July 1,	1993. FARMINGTON RESO	URCE AREA SEP	
8. I hereby certify that the foregoing is true and correct Signed and Correct TITLE (Temp.) Production Tech DATE OPEN 19/21/92 APPROVED BY TITLE DATE DATE		٠,			E B C C
STONE OF FEDERAL OF State office use) FARMINGTON NEW MEXICO FARMINGTON NEW MEXICO TITLE (Temp.) Production Tech DATE DATE DATE			OCT 14"	1992	두말
8. I hereby certify that the foregoing is true and correct STONED THE TITLE (Temp.) Production Tech APPROVED BY					ri Pi
STONE OF Federal or State office use) APPROVED BY					: , •
(This space for Federal or State office use) APPROVED BY	8. I hereby certify that the foregoing is	true and correct	77 17		
(This space for Federal or State office use) APPROVED BY		There may p (Temp.	.) Production Tech	₹9/21	
APPROVED BY				_ DATE	
APPROVED BY TITLE DATE CONDITIONS OF APPROVAL, IF ANY:	, and apart to a contact or state out			•	
CONDITIONS OF ALLBOTAM, M. AND.	APPROVED BY	TITLE		DATE	
	CONDITIONS OF STREET, IF A	***		:	,
		*See Instructions of	on Poveme Side	, ,	

NMOCD

