

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/>		#158M 30-039-25057 #53 30-039-06978	
2. NAME OF OPERATOR Union Oil Company of California dba UNOCAL			
3. ADDRESS OF OPERATOR P.O. Box 850, Bloomfield, New Mexico 87413			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Rincon Unit 158M - 1535' FSL + 148 FEL Rincon Unit 53 - 1750' FSL + 1690 FEL			
14. PERMIT NO		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6426' GL, 6430 GR	
		OIL CON. DIV. DIST. 3	
5. LEASE DESIGNATION AND SERIAL NO. SF - 079366		6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A	
7. UNIT AGREEMENT NAME Rincon Unit		8. FARM OR LEASE NAME Rincon Unit	
9. WELL NO. 158 M, 53		10. FIELD AND POOL, OR WILDCAT Blanco MV, Basin DK Blanco S-PC	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 22, T27N, R6W Sec 22, T27N, R6W		12. COUNTY OR PARISH Rio Arriba	
		13. STATE NM	

16 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PCLL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other) Install Cathodic Protection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Proposed installation of Cathodic Protection to well casing:

PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeze (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze.

A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existing roads and locations. See attached map.

UNOCAL's completion expectation is July 1, 1993.

ACCEPTED FOR RECORD
FARMINGTON RESOURCE AREA

OCT 14 1992

FARMINGTON, NEW MEXICO

18 I hereby certify that the foregoing is true and correct

SIGNED

Donald E. Lenthicum

TITLE

(Temp.) Production Tech

BY

DE

DATE

9/21/92

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCD

ON UNIT

