30-045-06680

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

Operator BHP Petroleum (americar), Inc. Location: Unit G Sec. 12 Twp 21 N Rng 11 W
Name of Well/Wells or Pipeline Serviced E.H. Piptin 12
Elevation 5897kg Completion Date 5/24/6! Total Depth 6356 Land Type* F-5F078019
Casing, Sizes, Types & Depths Surface: 85/8" 20pt 8V X-52 set at 341'
Production: 41/2 9.5 ppf 8R J-55 set at 6348'
If Casing is cemented, show amounts & types used Surface: 2005x5 Production: 157 stage
375 sxs, 2° Mostage - 150 sxs; 27/8" that w/ retainer set 2 6141 contid to surface 7/65
If Cement or Bentonite Plugs have been placed, show depths & amounts used
Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. unavailable
Depths gas encountered: 62/4'-62/9': 6232'-6236' DEFE VED
Type & amount of coke breeze used: unavailable
Depths anodes placed: unavailable ON COM DIA
Depths vent pipes placed: unavaicable DIST. 3
Vent pipe perforations: unavailable
· · · · · · · · · · · · · · · · · · ·
information concerning cathodic protection
If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.
*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.