

622

30-039-22213

E
2244WDATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Location: Unit 0 Sec. 30 Twp 30 Rng 6Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6#S1AElevation _____ Completion Date 8-7-91 Total Depth 441 Land Type FCasing Strings, Sizes, Types & Depths 8" PVC CASING 100' DEEPIf Casing Strings are cemented, show amounts & types used 20 BAGSNEAT CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NODepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 220' (DAMP)Depths gas encountered: NOGround bed depth with type & amount of coke breeze used: 441' DEEPwith 132 (5016) BAGS of Asbury 4518 Flo CokeDepths anodes placed: 425, 415, 405, 395, 385, 375, 365, 355, 346, 300, 290, 255Depths vent pipes placed: 441Vent pipe perforations: bottom 300'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 244	P/L NAME(S), NUMBER(S) SAN JUAN 30-6 #51-A					
WD #	TOTAL	VOLTS	AMPS	= OHMS	DATE	NAME
		10.88	18.8	.58	8-7-91	M RW
REMARKS (notes for construction log)						
100' 8" 20 BAGS						
H ₂ O 220' NOT ENOUGH for sample 132 BAGS Asbury 4518						

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100			295	3.1		490			685			
105			300	2.8-		495			690			
110			305	2.6		500			695			
115			310	2.4		505			700			
120			315	1.6		510			ANODE	DEPTH	NO	FULLY
125			320	1.4		515			#		COKE	COKE'D
130			325	1.3		520			1	425	2.9	5.6
135			330	1.4		525			2	415	3.3	5.9
140			335	1.5		530			3	405	3.1	5.5
145			340	1.5		535			4	395	2.8	4.9
150			345	2.1-		540			5	385	2.7	4.4
155			350	3.1		545			6	375	3.3	4.7
160			355	3.6-		550			7	365	3.0	5.0
165			360	3.4		555			8	355	3.7	5.3
170			365	3.0-		560			9	346	2.7	4.4
175			370	3.2		565			10	300	3.0	5.1
180			375	3.3-		570			11	296	3.1	5.1
185			380	2.8		575			12	255	3.2	5.0
190			385	2.7-		580			13			
195			390	2.7		585			14			
200			395	2.8-		590			15			
205			400	3.2		595			16			
210			405	3.0-		600			17			
215			410	3.3		605			18			
220	1.		415	3.3-		610			19			
225	1.3		420	3.2		615			20			
230	1.8		425	2.8-		620			21			
235	2.6		430	2.7		625			22			
240	2.5		435	1.6		630			23			
245	2.3		440	FD	441	635			24			
250	3.0		445			640			25			
255	3.0-		450			645			26			
260	2.8		455			650			27			
265	2.4		460			655			28			
270	2.0		465			660			29			
275	1.9		470			665			30			
280	2.0		475			670						
285	2.6		480			675						
290	3.0-		485			680						

DISTRIBUTION - original - permanent CPS FILE

COPY - Division Corrosion Supervisor

COPY - Region Corrosion Specialist