

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

APR 24 2008

Bureau of Land Management
Farmington Field Office

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit C (NENW), 1038' FNL & 1760' FWL, Sec. 5, T27N, R8W, NMPM

5. Lease Number
USA SF-0784616. If Indian, All. or
Tribe Name

7. Unit Agreement Name

RCUD MAY 7 '08

OIL CONS. DIV.

DIST. 3

8. Well Name & Number

Filan 5M

9. API Well No.

30-045-34474

10. Field and Pool

Basin Dakota/Blanco Mesaverde

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action


☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing Report☒ Subsequent Report☐ Plugging☐ Non-Routine Fracturing☐ Final Abandonment☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection

13. Describe Proposed or Completed Operations

MIRU H&P 283. PT csg to 600#/30 mins - test good. ✓ RU 8 3/4" bit. Tagged on cmt @ 200' & D/O. Drill ahead to 4150' intmed TD. Interm TD reached 4/14/08. Circ hole. RIH w/100 jts 7", 20#, J-55 ST&C/LT&C csg & set @ 4097'. Pre-flush w/10/10/10. Pump Lead 564 sx (1201 cf - 214 bbls slurry) Premium Lite FM, w/.4% Sodium Metasilicate, 3% CALCL2, 5#/sx LCM-1, 8% Bentonite, .4% FL-52A, .25#/sx Cello flakes. Tail 96 sx (133 cf - 24 bbls slurry) Type III, w/1% CALCL2, .2% FL-52A, .25#/sx Cello flakes. Dropped plug & displaced w/164 bbls FW. Bumped plug to 2020# @ 2330 hrs 4/15/08. Circ 80 bbls cmt to surface. 4/16/08 @0800 hrs PT csg to 1500#/15 mins - test good. ✓

4/16/08 RIH w/6 1/4" bit. Tagged cmt @ 4051' & D/O. Drilled ahead to 6811' TD. TD reached 4/17/08. Circ hole. RIH w/172 jts, 4 1/2", 10.5#, J-55 ST&C csg & set @ 6809'. Pre-flush 10 bbls gelled water & 2 bbls FW. Pumped Tail 208 sx (412 cf - 56 bbls slurry) Premium Lite HS FM, w/.4% Sodium Metasilicate, 3% CALCL2, 5#/sx LCM-1, 8% Bentonite, .4% FL-52A, .25#/sx Cello flakes. Dropped plug & displaced w/108 bbls FW w/ 1st 10 bbls w/sugar. Bumped plug to 1500# @ 0930 hrs 4/18/08. ND BOP & NU WH. RD & RR 4/18/08

PT will be conducted by the completion rig & recorded on the next report. TOC will be recorded on the next report. ✓



14. I hereby certify that the foregoing is true and correct.

Signed Rhonda Rogers Rhonda Rogers Title Regulatory Technician Date 4/24/08

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD