

#9A 30-045-2164

#23 30-045-22270

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

676

Operator Meridian Oil Inc Location: Unit I Sec 35 Twp 31 Rng 9

Name of Well/Wells or Pipeline Serviced Johnston Fed #53 and
#9A 2314-W

Elevation 2112 Completion Date 10-27-91 Total Depth 337 Land Type F

Casing Strings, Sizes, Types & Depths Set 100 of 8" P.O.C.

If Casing Strings are cemented, show amounts & types used Used 50
sacks of neat cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used
337' to 230' (25 sacks) 115' to 95' (6 sacks)

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 110' and was clear

Depths gas encountered: 280'

Ground bed depth with type & amount of coke breeze used: 230' with
22 sacks of Loresco - SW

Depths anodes placed: #1 is at 187' and #2 is at 130'

Depths vent pipes placed: 187' to surface

Vent pipe perforations: 187' up to 130'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2314-W	P/L NAME(s), NUMBER(s) Johnston Fed #73 #9A					
ID #	TOTAL	VOLTS	AMPS	= OHMS	DATE	NAME
		12.05	24.9		10-26-91	R. Smith

REMARKS (notes for construction log)

H₂O is at Drilled
to 337 and had a large amount of gas. Put
25 bags of cement in bottom of hole to
stop gas (approx 100' plug). Vent perforated to 130'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100	2.5		295	2.7		490			685			
105	2.4		300	2.6		495			690			
110	2.8		305	2.4		500			695			
115	3.0		310	1.8		505			700			
120	3.4		315	1.3		510			ANODE	DEPTH	NO.	FULLY
125	3.3		320	1.2		515			*		COKE	COKE D
130	3.2		325	1.4		520			1	187	4.8	6.0
135	3.3		330	1.2		525			2	180	5.4	8.5
140	3.0		335	1.0		530			3	175	5.3	10.4
145	3.1		340	10 337		535			4	170	5.6	10.4
150	3.5		345			540			5	165	5.0	10.8
155	3.6		350			545			6	160	5.5	11.1
160	3.3		355			550			7	155	5.3	10.7
165	2.8		360			555			8	150	5.3	9.6
170	3.2		365			560			9	145	5.1	9.2
175	3.4		370			565			10	140	5.0	7.7
180	2.8		375			570			11	135	5.0	7.6
185	2.0		380			575			12	130	5.2	8.4
190	1.1		385			580			13			
195	1.0		390			585			14			
200	1.1		395			590			15			
205	.8		400			595			16			
210	.9		405			600			17			
215	1.3		410			605			18			
220	1.0		415			610			19			
225	1.0		420			615			20			
230	1.3		425			620			21			
235	.9		430			625			22			
240	.7		435			630			23			
245	.8		440			635			24			
250	.8		445			640			25			
255	1.2		450			645			26			
260	1.9		455			650			27			
265	1.8		460			655			28			
270	1.4		465			660			29			
275	1.2		470			665			30			
280	1.3		475			670						
285	1.3		480			675						
290	1.0		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist