

30-039-24392

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Moradine Oil Location: Unit H Sec. 22 Twp 31 Rng 6

Name of Well/Wells or Pipeline Serviced Luna # 301

Elevation 6250 Completion Date 10-28-91 Total Depth 405' Land Type F

Casing Strings, Sizes, Types & Depths 60" 40' 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO

OIL CON. DIV.

DIST. 3

Ground bed depth with type & amount of coke breeze used:

445' Refuse, 75 sacks

Depths anodes placed: 400, 385, 370, 360, 350, 340, 310, 275, 265, 255, 245, 23

Depths vent pipes placed: 385'

Vent pipe perforations: 1" apart Perforated bottom 280

Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	9029					
P/L NAME(s), NUMBER(s)	Lasa # 201					
WO #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
J181		12.46	23.2	.53	10-28-91	L.S.E.

REMARKS (notes for construction log)

NO Water Table, Dry hole, Set 60' of 8" PVC casing.
Perforated bottom 280' from 2nd anode.

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
100	1.7		295	1.6		490			685			
105	1.7		300	1.4		495			690			
110	1.7		305	1.5		500			695			
115	2.2		310	2.4	- 7	505			700			
120	2.3		315	2.3		510			ANODE	DEPTH	NO	FULL
125	2.6		320	2.2	- 4	515			*		COKE	COK*
130	2.4		325	1.9		520			1	400	2.2	4.2
135	2.0		330	1.9		525			2	335	2.2	4.3
140	1.2		335	1.9		530			3	370	2.7	4.9
145	1.0		340	2.2		535			4	360	2.6	5.2
150	1.1		345	2.2		540			5	350	2.5	5.2
155	1.1		350	2.4	- 5	545			6	320	2.2	4.5
160	1.1		355	2.7		550			7	310	2.5	4.7
165	1.0		360	2.6	- 4	555			8	275	2.5	5.7
170	1.2		365	2.7		560			9	265	2.6	6.1
175	2.1		370	2.7	- 3	565			10	255	2.7	5.7
180	1.8		375	2.3		570			11	245	3.1	6.1
185	2.2		380	2.1		575			12	230	3.1	6.0
190	2.3		385	2.2	- 2	580			13			
195	2.6		390	2.0		585			14			
200	2.4		395	2.1		590			15			
205	2.2		400	2.2	- 1	595			16			
210	1.4		405	2.0		600			17			
215	1.3		410	1.4		605			18			
220	1.9		415	1.2		610			19			
225	2.8		420	1.2		615			20			
230	3.2	- 12	425	1.1		620			21			
235	3.0		430	1.0		625			22			
240	2.8		435	1.1		630			23			
245	3.0	- 11	440	.9		635			24			
250	2.9		445	TD	445	640			25			
255	2.7	- 10	450			645			26			
260	2.5		455			650			27			
265	2.6	- 9	460			655			28			
270	2.8		465			660			29			
275	2.5	- 8	470			665			30			
280	2.1		475			670						
285	1.7		480			675						
290	2.0		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist