

720

30-039-24426 E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

90306

Operator Mission Oil Location: Unit D Sec. 23 Twp 51 Rng 6

Name of Well/Wells or Pipeline Serviced Line # 23

Elevation 285 Completion Date 10-27-91 Total Depth 392 Land Type F

Casing Strings, Sizes, Types & Depths 60" 40' 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO

OIL CON. DIV
DIST

Ground bed depth with type & amount of coke breeze used:

392' Ashbury 33 sacks

Depths anodes placed: 375 365 355 345 335 325 315 305 295 285 275 265

Depths vent pipes placed: 365

Vent pipe perforations: 1" apart Perforated bottom 280'

Remarks: from 2nd anode

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(S), NUMBER(S)					
9030	Kasa - 213					
WO #	TOTAL	VOLTS	AMPS	= OHMS	DATE	NAME
6625		12.44	16.8	.74	10-27-91	L.S.E.

REMARKS (notes for construction log)

No Water Table, Dry hole. Set 60' of 8" PVC casing.
Perforated bottom 280' from 2nd anode.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE	*		ANODE	*		ANODE	*		ANODE	*
100	2.0		295	2.9	- 7	490			685		
105	1.1		300	2.7		495			690		
110	.9		305	2.5	- 5	500			695		
115	1.7		310	2.2		505			700		
120	2.1		315	1.8	- 7	510			ANODE	DEPTH	NO.
125	2.0		320	2.0		515			*		FULL
130	2.0		325	2.4	- 6	520				COKE	COKE
135	1.3		330	2.1		525			1	375	1.8
140	1.6		335	2.2	- 5	530			2	365	1.8
145	2.2		340	2.5		535			3	355	2.0
150	1.5		345	2.1	- 4	540			4	345	2.3
155	1.0		350	2.1		545			5	335	2.2
160	.7		355	2.0	- 3	550			6	325	2.3
165	.7		360	1.8		555			7	315	2.0
170	.8		365	1.8	- 2	560			8	305	2.5
175	1.0		370	1.7		565			9	295	2.8
180	1.2		375	1.8	- 1	570			10	285	2.7
185	1.1		380	1.8		575			11	275	2.7
190	.8		385	1.7		580			12	265	2.2
195	.7		390	TD	392	585			13		
200	.9		395			590			14		
205	.9		400			595			15		
210	.9		405			600			16		
215	1.2		410			605			17		
220	1.5		415			610			18		
225	1.2		420			615			19		
230	1.0		425			620			20		
235	1.0		430			625			21		
240	.9		435			630			22		
245	.9		440			635			23		
250	1.0		445			640			24		
255	1.5		450			645			25		
260	1.8		455			650			26		
265	2.2	- 12	460			655			27		
270	2.5		465			660			28		
275	3.0	- 11	470			665			29		
280	2.9		475			670			30		
285	2.7	- 10	480			675					
290	2.9		485			680					

DISTRIBUTION -- original -- permanent CPS FILE
 copy -- Division Corrosion Supervisor
 copy -- Region Corrosion Specialist