

615

30-039-24494

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Mesdian Oil Location: Unit 6 Sec. 12 Twp 31 Rng 6Name of Well/Wells or Pipeline Serviced Line # 226CPS#2284Elevation 6285 Completion Date 10-16-91 Total Depth 490 Land Type FCasing Strings, Sizes, Types & Depths 60' 4" 40' 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NODepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NOOIL CON. DIV.
DIST. 3

Ground bed depth with type & amount of coke breeze used:

490' Ashbury 97 sacksDepths anodes placed: 450 425 370 355 342 325 310 295 283 260 245 230 215Depths vent pipes placed: 425' 195' 175'Vent pipe perforations: 1" apart Perforated bottomRemarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s)					DATE	NAME
2284	Loss # 226					10-16-91	L.S.E.
NO	TOTAL	VOLTS	AMPS	- OHMS			
J186		12.48	25.7	.48			

REMARKS (notes for construction log)

No water table. Dry hole. Set 60' of 9" PVC casing.
Perforated bottom 280' from 2nd anode.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100	2.5		295	2.9	-8	490	TD	490	685			
105	2.4		300	2.8		495			690			
110	2.4		305	2.5		500			695			
115	2.2		310	2.7	-7	505			700			
120	1.6		315	2.7		510			ANODE	DEPTH	NO	FULLY
125	1.6		320	2.8		515			*		COKE	COKE D.
130	1.6		325	2.5	-6	520			1	450	2.0	4.0
135	1.7		330	2.4		525			2	425	2.1	3.9
140	1.8		335	2.4		530			3	370	2.7	4.4
145	1.9		340	2.5	-5	535			4	355	2.7	4.8
150	2.1		345	2.7		540			5	342	2.6	4.7
155	2.1		350	2.5		545			6	325	3.0	5.2
160	2.1		355	2.6	-4	550			7	310	2.8	5.1
165	2.1		360	2.6		555			8	295	3.0	5.4
170	2.9		365	2.7		560			9	283	3.0	5.3
175	2.9	-15	370	2.6	-3	565			10	260	3.0	5.3
180	3.1		375	1.9		570			11	245	3.2	5.8
185	2.9		380	1.4		575			12	230	3.0	5.6
190	2.7		385	1.4		580			13	215	3.1	5.4
195	2.8	-14	390	1.7		585			14	195	2.9	5.9
200	2.6		395	1.8		590			15	175	3.0	6.1
205	2.7		400	1.7		595			16			
210	3.1		405	1.5		600			17			
215	2.9	-13	410	1.6		605			18			
220	2.8		415	1.5		610			19			
225	2.8		420	1.6		615			20			
230	3.0	-12	425	2.0	-2	620			21			
235	3.2		430	1.9		625			22			
240	3.2		435	1.7		630			23			
245	3.0	-11	440	1.7		635			24			
250	2.8		445	1.9		640			25			
255	3.0		450	2.0	-1	645			26			
260	2.9	-10	455	1.7		650			27			
265	2.5		460	1.6		655			28			
270	1.8		465	1.5		660			29			
275	1.6		470	1.2		665			30			
280	2.6	-9	475	1.1		670						
285	3.0		480	1.0		675						
290	3.0		485	1.0		680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist