

693

30-039-24962 E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

239524322W

Operator Meridian Oil Location: Unit B Sec. 20 Twp 31 Rng 5Name of Well/Wells or Pipeline Serviced Lusa # 321Elevation 553 Completion Date 10-8-91 Total Depth 488' Land Type FCasing Strings, Sizes, Types & Depths 60" 114 40 8" P.V.C.

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NODepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO

OIL CON. DIV.

Ground bed depth with type & amount of coke breeze used: DIST 3488' Ashurst, 104 sacksDepths anodes placed: 425, 385, 360, 350, 335, 315, 305, 255, 245, 235, 225, 175Depths vent pipes placed: 385'Vent pipe perforations: 1" apart, Perforated bottom 300'Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2298-W	P/L NAME (S), NUMBER (S) Losa # 321					
# L651	TOTAL	VOLTS 12.45	AMPS 25.6	OHMS .48	DATE 10-8-91	NAME L.S.E.
REMARKS (notes for construction log)						
No water table, Dry hole. Set 60' of 8" PVC casing. Perforated bottom 300' from 2nd anode.						

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100	2		295	2.6		490			685			
105	1.6		300	2.5		495			690			
110	1.0		305	2.9	-7	500			695			
115	1.5		310	3.0		505			700			
120	2.1		315	2.9	-6	510			ANODE	DEPTH	NO	FULLY
125	2.2		320	2.3		515			#		COKE	COKE D
130	2.1		325	2.5		520			1	425	2.9	5.5
135	1.6		330	2.7		525			2	385	2.9	5.3
140	1.8		335	2.9	-5	530			3	360	3.3	6.0
145	1.8		340	2.9		535			4	350	3.2	5.7
150	1.7		345	3.0		540			5	335	3.0	5.1
155	2.1		350	3.1	-4	545			6	315	3.0	5.1
160	1.8		355	3.2		550			7	305	3.0	5.0
165	2.0		360	3.1	-3	555			8	255	2.8	4.6
170	2.1		365	2.5		560			9	245	3.2	5.3
175	2.5	-12	370	2.2		565			10	235	3.0	5.1
180	1.9		375	2.0		570			11	225	3.3	5.3
185	1.0		380	2.5		575			12	175	2.7	4.3
190	1.8		385	3.0	-2	580			13			
195	1.2		390	2.7		585			14			
200	1.9		395	2.3		590			15			
205	2.1		400	2.0		595			16			
210	2.3		405	2.0		600			17			
215	2.6		410	2.1		605			18			
220	2.9		415	2.1		610			19			
225	3.0	-11	420	2.6		615			20			
230	2.6		425	2.9	-1	620			21			
235	2.8	-10	430	2.6		625			22			
240	2.9		435	2.6		630			23			
245	3.1	-9	440	2.6		635			24			
250	2.6		445	2.4		640			25			
255	2.7	-8	450	1.9		645			26			
260	2.1		455	1.9		650			27			
265	2.2		460	2.6		655			28			
270	2.2		465	2.7		660			29			
275	2.3		470	2.4		665			30			
280	2.6		475	2.5		670						
285	2.4		480	2.6		675						
290	2.0		485	TD	488	680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist