

667

30-039-24964

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc. Location: Unit K Sec. 34 Twp 31 Rng 5Name of Well/Wells or Pipeline Serviced Rosa 42702296-WElevation 6785 Completion Date 10-2-91 Total Depth 480 Land Type FCasing Strings, Sizes, Types & Depths Set 60' of 8" P.U.C.If Casing Strings are cemented, show amounts & types used 12 sacks
of neat cement.If Cement or Bentonite Plugs have been placed, show depths & amounts used
no plugsDepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. no waterRECEIVED
FEB 24 1992OIL CON. DIV.
DIST. 3Depths gas encountered: no gasGround bed depth with type & amount of coke breeze used: 480' with
84 sacks of Asburg 4518Depths anodes placed: #1 is at 455. & #12 is at 180'Depths vent pipes placed: 385' to surfaceVent pipe perforations: vent pipe is perforated up to 14'

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2296-u	F/L NAME(s), NUMBER(s) #270					
WO # L489	TOTAL	VOLTS 11.83	AMPS 56.3	- OHMS	DATE 10-2-91	NAME R. Smith

REMARKS (notes for construction log)

No H₂O, No sample

Vent perforated up to 140'

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE	*		ANODE	*		ANODE	*		ANODE	*
100	3.5		295	2.4		490			685		
105	3.4		300	2.4		495			690		
110	2.8		305	2.4		500			695		
115	2.6		310	2.4		505			700		
120	3.1		315	2.4		510			ANODE	DEPTH	NO.
125	3.6		320	2.8		515			*		FULL
130	3.8		325	2.8	(6)	520			1	455	2.6
135	3.6		330	2.5		525			2	385	3.4
140	3.8		335	2.8		530			3	370	3.9
145	3.7		340	3.0	(5)	535			4	355	3.4
150	3.7		345	3.1		540			5	340	3.5
155	3.5		350	3.1		545			6	325	3.1
160	3.1		355	3.1	(4)	550			7	285	3.0
165	3.5		360	3.3		555			8	240	2.4
170	3.5		365	3.3		560			9	225	3.7
175	3.2		370	3.6	(3)	565			10	210	3.7
180	3.1	(12)	375	3.2		570			11	195	3.6
185	3.0		380	2.8		575			12	180	3.2
190	3.0		385	3.2	(2)	580			13		
195	3.3	(11)	390	2.6		585			14		
200	3.3		395	2.7		590			15		
205	3.5		400	2.9		595			16		
210	3.4	(10)	405	2.4		600			17		
215	3.4		410	1.9		605			18		
220	3.4		415	1.8		610			19		
225	3.4	(9)	420	1.9		615			20		
230	3.5		425	1.8		620			21		
235	3.0		430	1.9		625			22		
240	3.1	(8)	435	2.2		630			23		
245	2.9		440	2.3		635			24		
250	2.8		445	2.0		640			25		
255	2.8		450	2.1		645			26		
260	2.3		455	2.6	(1)	650			27		
265	2.3		460	2.5		655			28		
270	2.2		465	2.4		660			29		
275	2.7		470	2.6		665			30		
280	3.0		475	2.4		670					
285	2.8	(7)	480	2.3		675					
290	2.5		485	TD		680					

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist