

30-045-10168

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator El Paso Field Services Location: Unit NE Sec. 25 Twp 31 Rng 11

Name of Well/Wells or Pipeline Served Wallace Gas com #119

Elevation _____ Completion Date _____ Total Depth 400 Land Type ^F * 00000

Casing, Sizes, Types & Depths 8 7/8 - P.V.C. 40'

If Casing is cemented, show amounts & types used 15 Bags Z1A Type 1 & 2

If Cement or Bentonite Plugs have been placed, show depths & amounts used —

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. Drill with water—

Depths gas encountered: _____


Type & amount of coke breeze used: coresco sw 4900 /bs

Depths anodes placed: 165 - 370

Depths vent pipes placed: 380

Vent pipe perforations: 200

Remarks: _____



If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

* Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

THE LOFTIS COMPANY

DATE: September 5, 1997

COMPANY: EPFS / Amoco

COUNTY: San Juan STATE: New Mexico

CONTRACT NO: FC - 96 - 1000

UNIT NO: CPS # 72090, WO # 2965

Wellname - Wallace GC #1A

GROUND BED: DEPTH / FT 400'

DIA / INCH: 7 7/8"

ANODES: (15) 2 X 60 SHA-2's

CASING: DEPTH / FT 40'

SIZE: 8"

DEPTH IN FEET	DRILLERS LOG	RESISTIVITY		ANODE NUMBER	DEPTH TO ANODE TOP	BEFORE COKE	AFTER COKE
		OHMS	AMPS				
5	Casing						
10							
15							
20							
25							
30							
35							
40	Casing		1.8				
45	Shale		3.1				
50			2.3				
55			2.0				
60			2.2				
65			2.1				
70			2.7				
75			2.9				
80			2.6				
85			2.5				
90			3.1				
95			3.3				
100			3.2				
105			3.7				
110			3.8				
115			4.5				
120			4.5				
125			4.3				
130			3.3				
135			3.1				
140			3.4				
145			2.9				
150			2.8				
155			2.7				
160			2.8				
165			2.9	15	165	2.9	7.0
170			2.8				
175			3.0	14	175	3.4	7.4
180			2.1				
185			2.0				
190			2.1				
195			1.7				
200			0.8				
205			0.7				
210	Sandstone		2.2				

JOB # TDM1350

THE LOFTIS COMPANY

DEPTH IN FEET	DRILLERS LOG	RESISTIVITY		ANODE NUMBER	DEPTH TO ANODE TOP	BEFORE COKE	AFTER COKE
		OHMS	AMPS				
215			2.6	13	215	2.9	7.2
220			2.5				
225			2.3	12	225	2.7	7.0
230			2.4				
235			2.6	11	235	2.7	7.0
240	Shale		2.7				
245			2.5	10	245	2.8	7.6
250			2.7				
255			2.5	9	255	2.7	7.4
260			2.5				
265			2.5	8	265	2.7	7.6
270			2.6				
275			2.3	7	275	2.5	7.4
280			2.5				
285			2.6	6	285	2.6	7.5
290			3.0				
295			2.4	5	295	2.9	8.0
300			1.6				
305			1.2				
310			1.4				
315			1.8				
320			1.6				
325			1.4				
330			1.4				
335			2.4				
340			2.8	4	340	2.8	6.9
345			2.5				
350			2.4	3	350	2.5	6.6
355			2.4				
360			2.5	2	360	2.5	6.2
365			2.4				
370			2.5	1	370	2.5	6.4
375			2.6				
380			2.3				
385			1.5				
390							
395							
400	Shale						