

#21 30-039-07047

#156 30-039-07034

#256 30-039-24561

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator UNOCAL Location: Unit Sec. 16 Twp 27 Rng 6

Name of Well/Wells or Pipeline Serviced Rincon Unit No. 156, 256(FC), 21(MV)

Elevation 6661' Completion Date 8/29/90 Total Depth 300' Land Type* P

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 80' deep, damp=5' thick, fresh

Depths gas encountered: NONE

Type & amount of coke breeze used: 300' deep with carbo-60=99.9 carbon coke breeze

Depths anodes placed: 220', 230', 240', 250', 260', 270'

Depths vent pipes placed: 0-300' deep

Vent pipe perforations: 80' to 300' deep

Remarks: 2nd ground bed installed at this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
JAN 30 1991
OIL CON. DIV.
DIST. 3

COMPANY Unocal JOB No. 751-00084 DATE: 8-29-90
 WELL: Rincon Unit No 156 PIPELINE: _____
 LOCATION: SEC. 16 TWP. 27 RGE. 6 CO. Rio Arriba STATE NM
 ELEV. 6661 FT: ROTARY 300 FT: CABLE TOOL _____ FT: CASING Coke Carbo 40
 GROUNDED: DEPTH 300 FT. DIA. 6" IN. GAS _____ LBS. ANODES 6 kida ST 1.6/50

DEPTH.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH, TOP OF ANODES
		E	I	R				
0-40'	Brown sand & chip shale							
40-60'	Brown sandstone Red & grey shale							
60	Frist water 80' Ramp		8					
100	Vent Pipe 80'		8					
5			1.0					
10			.5					
15			.7					
20	Grey sandstone w/ some shale		.7					
25			.8					
30			2.5					
35			2.5					
40			2.6					
45			2.3					
50			2.2					
55			1.9					
60			1.6					
65			1.6					
70	Grey to dark grey shale		1.6					
75			1.5					
80			1.5					
85			1.9					
90			2.1					
95			2.2					
200			2.2					
5			2.2					
10			2.5					
15			2.7					
20			2.8				6	
25			2.8					
30			2.7				5	
35			3.0					
40			3.2				4	
45			3.1					
50			2.8				3	
55			3.0					
60			2.8				2	
65			2.6					
70			2.2				1	
75			2.2					
80			1.8					
85			2.0					
90			1.7					
95			1.8					
300	T HO							
5								

GROUNDED RESISTANCE: (1) VOLTS 12.47 - AMPS 8.1 - 1.54 OHMS

(2) VIBROGROUND _____ OHMS

MO-TE DRILLING, INC.

DAY Wednesday

DRILLER <i>R.B.C.</i>		LEFT TOWN <i>8</i>	ARRIVED FIELD
-----------------------	--	--------------------	---------------

HELPER	<i>Curcio</i>	LEFT FIELD	ARRIVED TOWN
--------	---------------	------------	--------------

HELPER	<i>June L.</i>	TOTAL FOOTAGE TODAY
--------	----------------	---------------------

RIG NO. 201 DATE 8-29-90 CLIENT Clint. Cal

BEGIN WORK ON HOLE NO. Reelway 956 AT _____ FEET

BEGIN WORK ON HOLE NO. 156 AT _____ FEET

[illegible]

BIT RECORD		
SIZE & MAKE	SERIAL NO.	FOOTAGE
1 1/2" "	21023	Blades
CIRCULATION MATERIAL		
QUAN.	UNIT	MATERIAL

NO. OF LOADS OF WATER _____ SOURCE _____

san juan repr farm,nm Form 219-6