DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO

(Submit 3 Copies to OCD Aztec Office)

Operator: BLACKWOOD & NICHOLS CO. Location: Unit L, Sec. 30, Twp 31N, Rng 6W.
Name of Well/Wells or Pipeline Serviced NEBU 495, 62, 304
495-30-039-24621 62-30-039-18243 304-30-039-24/63
115 30037 2724 62 30037 11010 307 300037 31723
Elevation 6340' Completion Date 6-7-93 Total Depth 360' Land Type* Surface: F Mineral: NM-03357
C. ' C' T 9 D 9 C/OH CCTI 40 D.V.C 1001 7 7/01 O II-1-
Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C 100', 7-7/8" Open Hole
If Casing is cemented, show amounts & types used 20 sks Portland Zia I-II - 90# ea.
To casing is contented, show amounts at types used
If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A
Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A
Depths gas encountered: 330' (small amount of H ₂ S)
Time & amount of calls brooms used. Ashum Fla Calss 5 000#
Type & amount of coke breeze used: Asbury Flo-Coke - 5,000#
Depths anodes placed: 345' to 115' - 20 anodes
Depths anodes placed: 345' to 115' - 20 anodes Depths vent pipes placed: 1" Sch. 40 PVC 355'
Depths vent pipes placed: 1" Sch. 40 PVC 355' SEPI 61993
Vent pipe perforations: 355' to 115' OIL CON. DIV '
, DIST. 3
Remarks: Small amount of H ₂ S gas at 330', 260' 166° SW of 495 wellhead.
If any of the shows data is unevailable places indicate as. Comics of all local including Drillers I as
If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned
wells are to be included.
*Lond Time may be above. E Federal, I Indian C State: D Fee
*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.
,
Signed by: lames K. all Title: Operations Engineer Date: P/26/83

BLACKWOOD & NICHOLS CATHODIC GROUND BED DRILLERS REPORT

6/7/93

CP#<u>L-3</u> WELL# <u>495</u>, <u>304</u> +62

L s 30 T 31N R6

DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
0			340		
100		CASING	350		
110	Black Shale		360	V	
120					
130					
140					
150					
160					
1170	\		,		
180	GREY SANDSTONE				
190					
200					
210					
220	V				
230	Grey Shale				
240					• •
250					
260					
270	V				
290	GREY Shale +5.5				
290	1				
300	Grey Stale				
310	/				
320					
3 <i>30</i>	Hard Bhuc Room	Small AMOUNT of H25			

DRILLER	M	INSPECTOR