

30-039-24662

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator UNOCAL Location: Unit Sec. 18 Twp 27 Rng 6

Name of Well/Wells or Pipeline Serviced Rincon Unit No. 252

Elevation 6618' Completion Date 9/13/90 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 110' deep, damp=5' thick, fresh

Depths gas encountered: NONE

Type & amount of coke breeze used: 300' deep with carbo-60=99.9 carbon coke breeze.

Depths anodes placed: 215', 225', 235', 245', 255', 265'

Depths vent pipes placed: 0 to 300' deep

Vent pipe perforations: Laser vut slots from 100' to 300' deep.

Remarks: 2nd ground bed installed at this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
JAN 30 1991
OIL CON. DIV.
DIST. 3

COMPANY Unocal JOB No. 751-00084 DATE: 9-73-90
 WELL: Rincon N°252 PIPELINE: _____
 LOCATION: SEC. 18 TWP. 27 RGE. 6 CO. Rio Arriba STATE NM
 ELEV. 6618'6 FT: ROTARY 300 FT: CABLE TOOL _____ FT: CASING Carbo 40
 GROUNDED: DEPTH 300' FT. DIA. 6" IN. GAS _____ LBS. ANODES 214 ST 1.6/52

DEPTH.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPT TOP ANCE
		E	I	R				
0-80'	Brown Sandstone & Clay							
80-90'	Grey Sandstone							
100	Frist Water 110' Pump Vent Pipe Grey Shale		.6					
5			.8					
10			2.6					
15			2.2					
20	Grey Sandstone		2.6					
25			2.1					
30			2.6					
35			2.0					
40			2.4					
45			1.8					
50			1.8					
55			1.4					
60			1.3					
65			1.0					
70			.7					
75			.6					
80			.5					
85			.7					
90	Grey & Dark Grey Shale		.7					
95			1.1					
200			1.3					
5			1.6					
10			1.7					
15			2.0					6
20			2.0					
25			2.3					5
30			2.3					
35			2.6					
40			2.4				6.2	4
45			2.6					
50			2.3					3
55			2.3					2
60	Hard shale w/ some Sandstone		2.0					
65			2.1					1
70			1.9					
75			2.2					
80			1.8					
85			1.8					
90								
95								
300								
5								

GROUNDED RESISTANCE: (1) VOLTS 12.44 - AMPS 6.2 - 2.00 OHMS

(2) VIBROGROUND _____ OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUKENS COMPANY

MO-TE DRILLING, INC.

DAY Thursday

DRILLER

Oct 2

LEFT TOWN 7:00 ARRIVED FIELD 30

HELPER

Licinus

LEFT FIELD ARRIVED TOWN

HELPER

June

TOTAL FOOTAGE TODAY

RIG NO.

206

DATE _____

9-13-90

CLIENT

Chas. Cad

BEGIN WORK ON HOLE NO.

Rincon 252



FEET

BEGIN WORK ON HOLE NO.

A-

FEET

[illegible]

BIT RECORD			
SIZE & MAKE	SERIAL NO.	FOOTAGE	
1 1/2" E"	regional spec.		
CIRCULATION MATERIAL			
QUAN.	UNIT	MATERIAL	

NO. OF LOADS OF WATER

SOURCE

Louise Camp-