

30-039-24700

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator UNOCAL Location: Unit Sec. 30 Twp 27 Rng 6

Name of Well/Wells or Pipeline Serviced Rincon Unit No. 265

Elevation 6590' Completion Date 9/12/90 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 105' deep, damp=5' thick, fresh

Depths gas encountered: NONE

Type & amount of coke breeze used: 300' deep with carbo-60=99.9 carbon coke breeze

Depths anodes placed: 150', 160', 170', 180', 190', 200'

Depths vent pipes placed: 0 to 300' deep

Vent pipe perforations: Laser cut slots from 100' to 300' deep

Remarks: 1st ground bed installed at this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
JAN 30 1991
OIL CON. DIV
DIST. 3

DATA SHEET NO. 1061

COMPANY Unocal JOB No. 751-00084 DATE: 9-12-90
 WELL: Rincon Unit No 265 PIPELINE: _____
 LOCATION: SEC 30 TWP. 27 RGE. 6 CO. Rio Arriba STATE NM
 ELEV. _____ FT: ROTARY 300 FT: CABLE TOOL _____ FT: GASEING Carbo 40 ^{COKE} 40 ST 1.6/50
 GROUNDED: DEPTH 300' FT. DIA. 6" IN. GAS _____ LBS. ANODES _____

DEPTH. FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH. TOP OF ANODES
		E	I	R				
0-20	Red Shale & Sandstone							
20-40	Red Shale & Clay							
40-100	Grey Shale w/ Sandstone							
	<u>First water 105' Deep</u>							
100	Grey Sandstone			2.6				
5				2.7				
10	Grey & Dark Grey Shale			2.6				
5				2.5				
20				2.5				
5				2.5				
30				2.7				
5				2.4				
40				2.5				
5				2.4				
50				2.6				6
5				2.2				
60				3.0				5
5				2.8				
70				2.9		7.7		4
5				2.5				
80				2.6				3
5				2.4				
90				2.6				2
5				2.4				
200				2.6				1
5				2.5				
10				2.6				
5				2.8				
20	Grey Sandstone			2.5				
5				2.1				
30				2.0				
5				1.8				
40				1.8				
5				1.5				
50				1.4				
5				1.1				
60				1.1				
5				.8				
70				.8				
5				.6				
80				.7				
5				.6				
90				.5				
5				.7				
300	T & D 13							

GROUNDED RESISTANCE: (1) VOLTS 12.67 - AMPS 7.7 - 1.65 OHMS

(2) VIBROGROUND _____ OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUKENS COMPANY

NO. OF LOADS OF WATER SOURCE

TIME		FROM	TO	ACTIVITY
0	00			Boat work; sandstone
20	40			Reddish clay
40	100			Grey shale w/ sandstone
100	110			grey sandstone
110	220			Shale; Dark grey shale
220	200			grey sandstone

_____ AT _____ FEET
BEGIN WORK ON HOLE NO.

BEGIN WORK ON HOLE NO. 2-10-65 AT _____ FEET

RIG NO. 006 DATE 4-18-78 CLIENT UN-12

HELPER		TOTAL FOOTAGE TODAY
--------	--	---------------------

HELPER		LEFT FIELD	ARRIVED TOWN
--------	--	------------	--------------

DRILLER	01-10-10	LEFT TOWN. 0800	ARRIVED FIELD. 0830
---------	----------	-----------------	---------------------

DAY Wednesday