

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS

NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

30-039-25210

Operator: UNOCAL – Bloomfield, NM Location: Unit F Sec. 32 Twp. 27N Rng. 6W

Name of Well/Wells or Pipeline Served: RINCON UNIT 166E DK/MV

Elevation: 6526 GR Completion Date: 09/27/95 Total Depth: 300' Land Type* S

Casing, Sizes, Types & Depths: 6" PVC 0' TO 20'

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: MOIST AT 80'

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2500 LBS., SWB PETROLEUM COKE

Depths anodes placed: 115' 120' 125' 175' 180' 185' 210' 215' 220' 255'

Depths vent pipes placed: 0' – 300', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee
If Federal or Indian, add Lease Number.

RECEIVED
NOV - 8 1995
OIL CON. DIV.
DIST. 3

Chyrcial

DAILY DRILLING REPORT

9/26

1995

166E

Rincon Unit

NW of 32

27N

6W

N. 9

HOLE MADE:

300'

DESCRIPTION OF FORMATION

REMARKS:

REMARKS: hole had some moisture at 80'
Set 20' 6" PVC casing due to fill caving in / rocks.

Dear E. Burge

Driller

Tool Dresser