

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

149M - 30-039-25432

19- 30-039-06903

Operator: UNOCAL - Bloomfield, NM Location: Unit F Sec. 30 Twp. 27N Rng. 6W

Name of Well/Wells or Pipeline Served: RINCON UNIT 149M DK/MV, RINCON UNIT 19 FC

Elevation: 6709 GR Completion Date: 09/28/95 Total Depth: 300' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: DRY/ NO MOISTURE

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2500 LBS., SWB PETROLEUM COKE

Depths anodes placed: 165' 173' 200' 210' 220' 255' 261' 268' 275' 283'

Depths vent pipes placed: 0' - 300', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F - Federal; I - Indian; S - State; P - Fee
If Federal or Indian, add Lease Number.

RECEIVED
NOV - 8 1995
OIL CON. DIV.
DIST. 3

Cathodic Protection Services

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 751-00355	P/L NAME(s), NUMBER(s) Rincon Unit 149 m					DATE 9/28/95	NAME Don L.
WO #	TOTAL 10 Anodes	VOLTS 13.8	AMPS 16.5	= OHMS .83			

REMARKS (notes for construction log)

300' of 1" PVC 200' perforated / 2500' of coke

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	
100	1.0		295	.5		490			685			
105	1.0		300	T.O.		495			690			
110	1.0		305			500			695			
115	1.0		310			505			700			
120	1.2		315			510			ANODE	DEPTH	NO	FULL
125	.9		320			515			#		COKE	COKE
130	1.1		325			520			1	283	.9	1.8
135	1.1		330			525			2	275	1.0	2.8
140	1.1		335			530			3	268	.9	3.1
145	1.3		340			535			4	261	1.0	2.9
150	1.2		345			540			5	255	1.0	2.3
155	1.3		350			545			6	220	1.2	4.4
160	1.2		355			550			7	210	1.1	4.1
165	1.5		360			555			8	200	1.2	4.2
170	1.3		365			560			9	173	1.3	5.9
175	1.2		370			565			10	165	1.5	5.9
180	1.0		375			570			11			
185	1.0		380			575			12	2310		
190	.8		385			580			13	190		
195	1.2		390			585			14	2500		
200	1.2		395			590			15			
205	1.2		400			595			16			
210	1.0		405			600			17			
215	1.1		410			605			18			
220	1.2		415			610			19			
225	.8		420			615			20			
230	.5		425			620			21			
235	.4		430			625			22			
240	.3		435			630			23			
245	.3		440			635			24			
250	.4		445			640			25			
255	1.0		450			645			26			
260	1.0		455			650			27			
265	.9		460			655			28			
270	.8		465			660			29			
275	.8		470			665			30			
280	1.0		475			670						
285	.5		480			675						
290	.5		485			680						

