

30-045-05794

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 2 copies to OCD Aztec Office)

Operator Dugan Production Location: Unit B Sec. 19 Twp. 24N Rng 13W

Name of Well/Wells or Pipeline Serviced No. 107 WEST Bist. Unit

Elevation _____ Completion Date 3/23/81 Total Depth 300 Land Type* I

Casing, Sizes, Types & Depths NA-None

If Casing is cemented, show amounts & types used NA

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NA

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. Small trace of moisture at

50 FT. Depth.

Depths gas encountered: NA-None

Type & amount of coke breeze used: Metallurgical Coke = 2,760 LBS.

Depths anodes placed: 170', 180', 190', 200', 210', 220', 230', 240', 250', 260' Deep

Depths vent pipes placed: From 0' to 300' Deep.

Vent pipe perforations: From 160' to 300' Deep w/ 1/8" dia. holes every foot.

Remarks: NA-None

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.