

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 Copies to OCD Aztec Office)

ME-3

Operator: BLACKWOOD & NICHOLS CO. Location: Unit B, Sec. 12, Twp 31N, Rng 7W.

Name of Well/Wells or Pipeline Served NEBU 492 30-045-29660

Elevation 6600 Completion Date 8-3-93 Total Depth 450' Land Type* Surface: F Mineral: NM-00358

Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C. - 100', 7-7/8" Open Hole

If Casing is cemented, show amounts & types used 20 sks Portland Zia I-II - 90# ea.

If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. No sample.

Depths gas encountered: N/A

Type & amount of coke breeze used: 130 sx Asbury Recarburized Flo-Coke

Depths anodes placed: 335' - 425'

Depths vent pipes placed: 450' to 4' above ground level

Vent pipe perforations: 90' - 450'

Remarks: Ground bed is located 203' N 74° W of NEBU #492.

RECEIVED
SEP 1 6 1993
OIL CON.
DIST ?

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

Signed by: James K. Ahl

Title: Operations Engineer Date: 8/27/93

BLACKWOOD & NICHOLS
CATHODIC GROUND BED
DRILLERS REPORT

CP# ME-3 WELL# NERU 492

S 12 T 31N R 7W

DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
5'					
10'					
15'	↑				
20'					
25'					
30'					
35'					
40'					
45'	F				
50'	L				
55'	A				
60'	H				
65'	S				
70'					
85'					
90'					
95'					
100'	✓				

DRILLER Gene Muntz

INSPECTOR Joe Matysak

BLACKWOOD & NICHOLS
CATHODIC GROUND BED
DRILLERS REPORT

WP# ME#3 WELL# NEBU#492

S 12 T 31 R 5

[illegible]

DRILLER 

INSPECTOR J. E.