DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS

NORTHWESTERN NEW MEXICO (Submit 3 Copies to OCD Aztec Office)

4255

Operator: <u>BLACKWOOD & NICHOLS CO.</u> Location: Unit <u>C</u> , Sec. <u>20</u> , Twp <u>30N</u> , Rng <u>7W</u> .
Name of Well/Wells or Pipeline Serviced NEBU 479R, 13A
4192-30-039-25315 13A-30-039-22472
FEE Elevation 6300' Completion Date 12-10-93 Total Depth 475' Land Type* Surface: F Mineral: SF-079060
Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C 100'
If Casing is cemented, show amounts & types used18 sks Portland Zia I-II
If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A
Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. Clear, Standing water - 260'
Depths gas encountered: N/A
Type & amount of coke breeze used: Loresco - 7000#
Type & amount of coke breeze used: Loresco - 7000# Depths anodes placed: 265' - 425' (15) Oil CON. Division of Contract Contrac
Depths vent pipes placed: Bottom to 4' Above Ground Level
Vent pipe perforations: Bottom - 360'
Remarks: Groundbed Located at 91' 240°.from North of NEBU 479R wellhead.
If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.
*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.
Signed by K All Title: Operations Engineer Date: 1/3/96/

CATHODIC GROUND BED DRILLERS REPORT

\$5-10 _ WELL#_NEBU = 479R+ #13A s 20 r30-07 STRATA FÙL: $\mathbf{H}^{\mathbf{c}}$ STRATA NOTES DEPTH NOTES 0-10 Sandsone. Stole/5.5. 70-100 Sandstonen

LER_ Mark Bailes

INSPECTOR____

(D. E.)

WELL# NEBU # 4798-1317 C s 20 T 30-7 111 0-100 STRATA STRATA NOTES DEPTH

.ER____

INSPECTOR Mom